



SAFETY DATA SHEET

Issue Date 16-Oct-2019

Revision Date 24-Jul-2020

Version 2

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade name / designation PINK SANDS Wax Cube
Product Code 1676084E
Product Name WM-SGL PNK SNDS YCE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Consumer use
Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Supplier

Yankee Candle Company Europe Ltd.
Cabot Park, Poplar Way East, Avonmouth
Bristol, BS11 0YH, UK
Tel: +44(0) 117 316 1200

For further information, please contact

E-mail address SDSinfo@yankeecandle.com

1.4. Emergency telephone number

Emergency Telephone - §45 - (EC)1272/2008

Europe 008 008 658 8466

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [GHS]

2.2. Label elements

Contains Terpenes, Orange Oil, Limonene, Hexyl cinnamal, 5-Heptenal, 2,6-dimethyl-, Cyclamen aldehyde, Hexyl salicylate, Eugenol, Benzenemethanol, 4-methoxy-, 1-acetate May produce an allergic reaction

2.3. Other hazards

Contact with product at elevated temperatures can result in thermal burns

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2

Chemical Name	EC No	CAS No	Weight-%	Classification
---------------	-------	--------	----------	----------------

				according to Regulation (EC) No. 1272/2008 [CLP]
Paraffin waxes and Hydrocarbon waxes	232-315-6	8002-74-2	>=50%	No data available
Terpenes, Orange Oil		68647-72-3	>=0.1 <1%	Aquatic Acute 1 (H400) Skin Sens. 1B (H317) Skin Irrit. 2 (H315) Asp. Tox. 1 (H304) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226)
Propanol, oxybis-	246-770-3	25265-71-8	>=0.1 <1%	Not Classified
Cyclopenta[g]-2-benzopyran, 1,3,4,6,7,8-hexahydro-4,6,6, 7,8,8-hexamethyl-	214-946-9	1222-05-5	>=0.1 <1%	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Limonene	205-341-0	138-86-3	>=0.1 <1%	Flam. Liq. 3 (H226) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Skin Sens. 1B (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Hexyl cinnamal	202-983-3	101-86-0	>=0.1 <1%	Skin Sens. 1B (H317) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)
cis-3-Hexenyl Salicylate	265-745-8	65405-77-8	>=0.1 <1%	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
5-Heptenal, 2,6-dimethyl-	203-427-2	106-72-9	>=0.1 <1%	Skin Sens. 1B (H317)
Cyclamen aldehyde	203-161-7	103-95-7	>=0.1 <1%	Skin Irrit. 2 (H315) Skin Sens. 1B (H317) Aquatic Chronic 3 (H412)
Hexyl salicylate	228-408-6	6259-76-3	>=0.1 <1%	Skin Irrit. 2 (H315) Skin Sens. 1 (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Eugenol	202-589-1	97-53-0	>=0.1 <1%	Skin Sens. 1B (H317) Eye Irrit. 2 (H319)
Benzenemethanol, 4-methoxy-, 1-acetate	203-185-8	104-21-2	>=0.1 <1%	Skin Sens. 1B (H317)
1-Hexanol	203-852-3	111-27-3	>=0.01 <0.1%	Flam. Liq. 3 (H226) Acute Tox. 4 (H302) Acute Tox. 4 (H312) Eye Irrit. 2 (H319)
Acetic acid, butyl ester	204-658-1	123-86-4	>=0.01 <0.1%	EUH066 Flam. Liq. 3 (H226) STOT SE 3 (H336)
1-Butanol, 3-methyl-, 1-acetate	204-662-3	123-92-2	<0.01%	EUH066 Flam. Liq. 3 (H226) Aquatic Acute 3 (H402)
1,3,5-Undecatriene	240-416-1	16356-11-9	<0.01%	Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Citral	226-394-6	5392-40-5	<0.01%	Skin Irrit. 2 (H315) Skin Sens. 1 (H317) Eye Irrit. 2 (H319)
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl-	204-881-4	128-37-0	<0.01%	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Ethanol	200-578-6	64-17-5	<0.01%	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)
Benzenemethanol	202-859-9	100-51-6	<0.01%	Acute Tox. 4 (H302) Eye Irrit. 2 (H319) Acute Tox. 4 (H332)

Full text of H- and EUH-phrases: see section 16

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
Inhalation	Remove to fresh air.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Ingestion	Clean mouth with water and drink afterwards plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	None known.
-----------------	-------------

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
---------------------------	------------------------

Section 5: FIRE FIGHTING MEASURES**5.1. Extinguishing media****Suitable extinguishing media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

No information available

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating and toxic gases and vapors

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit. Use personal protective equipment as required.

Section 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures****Personal precautions**

Ensure adequate ventilation, especially in confined areas.

For emergency responders

Use personal protection recommended in Section 8.

6.2. Environmental precautions

Collect spillage.

6.3. Methods and material for containment and cleaning up

Methods for containment	Prevent further leakage or spillage if safe to do so.
--------------------------------	---

Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.
--------------------------------	---

6.4. Reference to other sections

See Section 12: ECOLOGICAL INFORMATION.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ensure adequate ventilation, especially in confined areas.

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Store at room temperature.

7.3. Specific end use(s)

To avoid risks to human health and the environment, comply with the instructions for use.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Chemical Name	European Union	United Kingdom	France	Spain	Germany
Paraffin waxes and Hydrocarbon waxes 8002-74-2		STEL: 6 mg/m ³ TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	
Propanol, oxybis- 25265-71-8					TWA: 100 mg/m ³ Ceiling / Peak: 200 mg/m ³
dipentene 138-86-3			TWA: 1000 mg/m ³ STEL: 1500 mg/m ³		
1-Hexanol 111-27-3					TWA: 50 ppm TWA: 210 mg/m ³
Acetic acid, butyl ester 123-86-4		STEL: 200 ppm STEL: 966 mg/m ³ TWA: 150 ppm TWA: 724 mg/m ³	TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 940 mg/m ³	STEL: 200 ppm STEL: 965 mg/m ³ TWA: 150 ppm TWA: 724 mg/m ³	TWA: 100 ppm TWA: 480 mg/m ³ Ceiling / Peak: 200 ppm Ceiling / Peak: 960 mg/m ³ TWA: 62 ppm TWA: 300 mg/m ³
1-Butanol, 3-methyl-, 1-acetate 123-92-2	TWA 50 ppm TWA 270 mg/m ³ STEL 100 ppm STEL 540 mg/m ³	TWA: 50 ppm TWA: 270 mg/m ³	TWA: 50 ppm TWA: 270 mg/m ³ STEL: 100 ppm STEL: 540 mg/m ³	STEL: 100 ppm STEL: 540 mg/m ³ TWA: 50 ppm TWA: 270 mg/m ³	TWA: 50 ppm TWA: 270 mg/m ³ Ceiling / Peak: 50 ppm Ceiling / Peak: 270 mg/m ³
1,3,5-Undecatriene 16356-11-9			TWA: 1000 mg/m ³ STEL: 1500 mg/m ³		
2,6-Octadienal, 3,7-dimethyl- 5392-40-5				S* TWA: 5 ppm	
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl- 128-37-0		STEL: 30 mg/m ³ TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³ Ceiling / Peak: 40 mg/m ³ Skin
Ethanol 64-17-5		STEL: 3000 ppm STEL: 5760 mg/m ³ TWA: 1000 ppm TWA: 1920 mg/m ³	TWA: 1000 ppm TWA: 1900 mg/m ³ STEL: 5000 ppm STEL: 9500 mg/m ³	STEL: 1000 ppm STEL: 1910 mg/m ³	TWA: 500 ppm TWA: 960 mg/m ³ Ceiling / Peak: 1000 ppm Ceiling / Peak: 1920 mg/m ³ Skin
Benzenemethanol 100-51-6					TWA: 22 mg/m ³ TWA: 5 ppm

					Ceiling / Peak: 44 mg/m³ Ceiling / Peak: 10 ppm Skin	
Chemical Name	Italy	Portugal	Netherlands	Finland	Denmark	
Paraffin waxes and Hydrocarbon waxes 8002-74-2		TWA: 2 mg/m³		TWA: 1 mg/m³	TWA: 2 mg/m³	
Acetic acid, butyl ester 123-86-4		STEL: 200 ppm TWA: 150 ppm		TWA: 150 ppm TWA: 720 mg/m³ STEL: 200 ppm STEL: 960 mg/m³	TWA: 150 ppm TWA: 710 mg/m³	
1-Butanol, 3-methyl-, 1-acetate 123-92-2	TWA: 50 ppm TWA: 270 mg/m³ STEL: 100 ppm STEL: 540 mg/m³	STEL: 100 ppm STEL: 540 mg/m³ TWA: 50 ppm TWA: 270 mg/m³	STEL: 530 mg/m³	TWA: 50 ppm TWA: 270 mg/m³ STEL: 100 ppm STEL: 540 mg/m³	TWA: 50 ppm TWA: 271 mg/m³	
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- 128-37-0		TWA: 2 mg/m³		TWA: 10 mg/m³ STEL: 20 mg/m³	TWA: 10 mg/m³	
Ethanol 64-17-5		TWA: 1000 ppm	Skin STEL: 1900 mg/m³ TWA: 260 mg/m³	TWA: 1000 ppm TWA: 1900 mg/m³ STEL: 1300 ppm STEL: 2500 mg/m³	TWA: 1000 ppm TWA: 1900 mg/m³	
Benzenemethanol 100-51-6				TWA: 10 ppm TWA: 45 mg/m³		
Chemical Name	Austria	Switzerland	Poland	Norway	Ireland	Czech Republic
Paraffin waxes and Hydrocarbon waxes 8002-74-2		TWA: 2 mg/m³	TWA: 2 mg/m³	TWA: 2 mg/m³ STEL: 4 mg/m³	TWA: 2 mg/m³ STEL: 6 mg/m³	
Propanol, oxybis- 25265-71-8		STEL: 280 mg/m³ TWA: 140 mg/m³				
dipentene 138-86-3				TWA: 25 ppm TWA: 140 mg/m³ TWA: 40 ppm TWA: 275 mg/m³ STEL: 37.5 ppm STEL: 175 mg/m³ STEL: 60 ppm STEL: 343.75 mg/m³		
Acetic acid, butyl ester 123-86-4	STEL 100 ppm STEL 480 mg/m³ TWA: 100 ppm TWA: 480 mg/m³ Ceiling 100 ppm Ceiling 480 mg/m³	STEL: 200 ppm STEL: 960 mg/m³ TWA: 100 ppm TWA: 480 mg/m³	STEL: 950 mg/m³ TWA: 200 mg/m³	TWA: 75 ppm TWA: 355 mg/m³ STEL: 112.5 ppm STEL: 418.75 mg/m³	TWA: 150 ppm TWA: 710 mg/m³ STEL: 200 ppm STEL: 950 mg/m³	Ceiling: 1200 mg/m³ TWA: 950 mg/m³
1-Butanol, 3-methyl-, 1-acetate 123-92-2	STEL 100 ppm STEL 540 mg/m³ TWA: 50 ppm TWA: 270 mg/m³	STEL: 50 ppm STEL: 260 mg/m³ TWA: 50 ppm TWA: 260 mg/m³	STEL: 500 mg/m³ TWA: 250 mg/m³	TWA: 50 ppm TWA: 260 mg/m³ STEL: 75 ppm STEL: 325 mg/m³	TWA: 50 ppm TWA: 260 mg/m³ STEL: 100 ppm STEL: 520 mg/m³	Ceiling: 540 mg/m³
1,3,5-Undecatriene 16356-11-9				TWA: 40 ppm TWA: 275 mg/m³ STEL: 60 ppm STEL: 343.75 mg/m³		
2,6-Octadienal, 3,7-dimethyl- 5392-40-5			STEL: 54 mg/m³ TWA: 27 mg/m³			
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- 128-37-0	TWA: 10 mg/m³	STEL: 40 mg/m³ TWA: 10 mg/m³			TWA: 10 mg/m³ STEL: 30 mg/m³	
Ethanol 64-17-5	STEL 2000 ppm STEL 3800 mg/m³ TWA: 1000 ppm TWA: 1900 mg/m³	STEL: 1000 ppm STEL: 1920 mg/m³ TWA: 500 ppm TWA: 960 mg/m³	TWA: 1900 mg/m³	TWA: 500 ppm TWA: 950 mg/m³ STEL: 625 ppm STEL: 1187.5 mg/m³	STEL: 1000 ppm	Ceiling: 3000 mg/m³ TWA: 1000 mg/m³
Benzenemethanol			TWA: 240 mg/m³			Ceiling: 80 mg/m³

100-51-6						TWA: 40 mg/m ³
----------	--	--	--	--	--	---------------------------

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering Controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Tight sealing safety goggles.
Skin and body protection Suitable protective clothing.

Environmental exposure controls No information available.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	Solid	Odor	Characteristic
Appearance	Candle and/or Wax	Odor threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH		Not Applicable
Melting point/freezing point	50-60 °C	No information available
Boiling point / boiling range		No information available
Flash point	>= 140 °C	No information available
Evaporation rate		No information available
Flammability (solid, gas)		No information available
Flammability Limit in Air		
Upper flammability limit:		No information available
Lower flammability limit:		No information available
Vapor Pressure @20°C (kPa)	No information available	No information available
Vapor density		No information available
Specific Gravity		No information available
Water solubility	negligible	No information available
Solubility(ies)		No information available
Partition coefficient		No information available
Autoignition temperature		No information available
Decomposition temperature		No information available
Kinematic viscosity		No information available
Dynamic viscosity		No information available
Explosive properties	No information available	
Oxidizing properties	No information available	

9.2. Other information

Softening point	No information available
Molecular weight	Not Applicable
VOC Content (%)	1.29
Density	No information available
Bulk density	No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

Stable under normal conditions.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

10.3. Possibility of hazardous reactions

None under normal processing.

10.4. Conditions to avoid

Extremes of temperature and direct sunlight.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

None under normal use conditions.

Section 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects****Product information**

Product does not present an acute toxicity hazard based on known or supplied information.

Unknown Acute Toxicity 8.1984% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document mg/kg

ATEmix (dermal) 78,261.00 mg/kg

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Paraffin waxes and Hydrocarbon waxes	> 5000 mg/kg (Rat)	> 3600 mg/kg (Rabbit)	
2,6-Octadienal, 3,7-dimethyl-	= 4960 mg/kg (Rat)	= 2250 mg/kg (Rabbit)	
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-	> 2930 mg/kg (Rat)	> 2000 mg/kg (Rat)	
Ethanol	= 7060 mg/kg (Rat)		= 124.7 mg/L (Rat) 4 h

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation Contact with eyes may cause irritation.

Sensitization Repeated or prolonged contact may cause allergic reactions in very susceptible persons.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Target Organ Effects Eyes, Respiratory system, Skin.

Aspiration hazard No information available.

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

9.549872% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Propanol, oxybis-		5000: 24 h Carassius auratus mg/L LC50 static	
1-Hexanol		89.7 - 106: 96 h Pimephales promelas mg/L LC50 flow-through 144: 96 h Brachydanio rerio mg/L LC50 static	201: 24 h Daphnia magna mg/L EC50
Acetic acid, butyl ester	674.7: 72 h Desmodemus subspicatus mg/L EC50	62: 96 h Leuciscus idus mg/L LC50 static 100: 96 h Lepomis macrochirus mg/L LC50 static 17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through	72.8: 24 h Daphnia magna mg/L EC50
2,6-Octadienal, 3,7-dimethyl-	19: 96 h Desmodemus subspicatus mg/L EC50 16: 72 h Desmodemus subspicatus mg/L EC50	4.6 - 10: 96 h Leuciscus idus mg/L LC50 static	7: 48 h Daphnia magna mg/L EC50
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-	6: 72 h Pseudokirchneriella subcapitata mg/L EC50 0.42: 72 h Desmodemus subspicatus mg/L EC50	5: 48 h Oryzias latipes mg/L LC50	
Ethanol		12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through	9268 - 14221: 48 h Daphnia magna mg/L LC50 10800: 24 h Daphnia magna mg/L EC50 2: 48 h Daphnia magna mg/L EC50 Static
Benzenemethanol	35: 3 h Anabaena variabilis mg/L EC50	460: 96 h Pimephales promelas mg/L LC50 static 10: 96 h Lepomis macrochirus mg/L LC50 static	23: 48 h water flea mg/L EC50

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Chemical Name	Partition coefficient
1-Hexanol	2.03
Acetic acid, butyl ester	1.81
2,6-Octadienal, 3,7-dimethyl-	2.76
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-	4.17
Ethanol	-0.32
Benzenemethanol	1.1

12.4. Mobility in soil

Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available

Section 13: DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods****Waste from Residues / Unused Products**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Improper disposal or reuse of this container may be dangerous and illegal.

Section 14: TRANSPORT INFORMATION**IMDG**

Proper shipping name

Not regulated

RID**ADR****ICAO (air)****IATA**

Proper shipping name

Not regulated

Section 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Chemical Name	French RG number	Title
Paraffin waxes and Hydrocarbon waxes 8002-74-2	RG 36	
dipentene 138-86-3	RG 84	
1-Hexanol 111-27-3	RG 84	
Acetic acid, butyl ester 123-86-4	RG 84	
1-Butanol, 3-methyl-, 1-acetate 123-92-2	RG 84	
Ethanol 64-17-5	RG 84	
Benzenemethanol 100-51-6	RG 84	

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

International Inventories**TSCA**

Complies

DSL/NDSL

Complies

EINECS/ELINCS

Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

AICS - Australian Inventory of Chemical Substances

15.2. Chemical safety assessment

No information available

Section 16: OTHER INFORMATION**Full text of H-Statements referred to under sections 2 and 3**

H302 - Harmful if swallowed

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H317 - May cause an allergic skin reaction

H400 - Very toxic to aquatic life

H411 - Toxic to aquatic life with long lasting effects

H315 - Causes skin irritation

H412 - Harmful to aquatic life with long lasting effects

H226 - Flammable liquid and vapor

H312 - Harmful in contact with skin

H410 - Very toxic to aquatic life with long lasting effects

H336 - May cause drowsiness or dizziness

H402 - Harmful to aquatic life

H304 - May be fatal if swallowed and enters airways

H225 - Highly flammable liquid and vapor

Classification procedure

Classification according to calculation method of the CLP regulation.

Key literature references and sources for data

IFRA-IOFI Labelling Manual, RIFM/FEMA database, Supplier Information

Issue Date 16-Oct-2019**Revision Date** 24-Jul-2020**Revision Note** Not Applicable.**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006****Disclaimer**

This document was prepared to the requirements of the jurisdiction specified in Section 2 above and may not meet regulatory requirements in other countries. The information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations. The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

End of Safety Data Sheet