

Version #: 01 Issue date: 28-June-2023

# SAFETY DATA SHEET

SECTION 1: Identification	of the substance/mixture and of the company/undertaking		
1.1. Product identifier Trade name or designation of the mixture	YC ICED BERRY LEMONADE REED DIFFUSER REFILL 1745740E		
Registration number Synonyms	- None.		
Product code	1745740E		
1.2. Relevant identified uses of Identified uses	the substance or mixture and uses advised against Air Care Products		
Uses advised against	None known.		
1.3. Details of the supplier of th	e safety data sheet		
Company name	Yankee Candle Company (Europe) Limited		
Company Address	Poplar Way East, Cabot Park		
	Avonmouth		
	Bristol		
	United Kingdom		
	BS11 0YH		
1.4. Emergency telephone numl General in EU	Der 112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)		
Austria National Poisons Information Centre	+431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)		
Belgium National Poisons Control Centre	070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)		
Bulgaria National Toxicological Information Centre	+359 2 9154233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)		
Czech Republic National Poisons Information Centre	+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)		
Denmark National Poisons Control Centre	+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)		
Estonia National Poisons Information Centre	16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)		
Finland National Poison Information Centre	(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)		
France National Poisons Control Centre	ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)		
Hungary National Emergency Phone Number	36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)		
Lithuania Neatidėliotina informacija apsinuodijus	+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)		
Malta Accident and Emergency Department	2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)		
Netherlands National Poisons Information Centre (NVIC)	030-274 88 88 (Only for the purpose of informing medical personnel in cases of acute intoxications)		

### 1.4. Emergency telephone number

Norway Norwegian Poison Information Centre	22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Portugal Poison Centre	800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Romania Biroul RSI si Informare Toxicologica	021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be available for the Emergency Service.)
Slovakia National Toxicological Information Centre	+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Sweden National Poison Information Centre	112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Switzerland Tox Info Suisse	145 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards Flammable liquids	Category 2	H225 - Highly flammable liquid and vapour.
Health hazards Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.

### 2.2. Label elements

# Label according to Regulation (EC) No. 1272/2008 as amended

UFI:

Austria: 2NHG-TAPW-AY2Q-0KRA Belgium: 2NHG-TAPW-AY2Q-0KRA Bulgaria: 2NHG-TAPW-AY2Q-0KRA Croatia: 2NHG-TAPW-AY2Q-0KRA Cyprus: 2NHG-TAPW-AY2Q-0KRA Czech Republic: 2NHG-TAPW-AY2Q-0KRA Denmark: 2NHG-TAPW-AY2Q-0KRA Estonia: 2NHG-TAPW-AY2Q-0KRA EU: 2NHG-TAPW-AY2Q-0KRA Finland: 2NHG-TAPW-AY2Q-0KRA France: 2NHG-TAPW-AY2Q-0KRA Germany: 2NHG-TAPW-AY2Q-0KRA Great Britain: 2NHG-TAPW-AY2Q-0KRA Greece: 2NHG-TAPW-AY2Q-0KRA Hungary: 2NHG-TAPW-AY2Q-0KRA Iceland: 2NHG-TAPW-AY2Q-0KRA Ireland: 2NHG-TAPW-AY2Q-0KRA Italy: 2NHG-TAPW-AY2Q-0KRA Latvia: 2NHG-TAPW-AY2Q-0KRA Lithuania: 2NHG-TAPW-AY2Q-0KRA Luxembourg: 2NHG-TAPW-AY2Q-0KRA Malta: 2NHG-TAPW-AY2Q-0KRA Netherlands: 2NHG-TAPW-AY2Q-0KRA Norway: 2NHG-TAPW-AY2Q-0KRA Poland: 2NHG-TAPW-AY2Q-0KRA Portugal: 2NHG-TAPW-AY2Q-0KRA Romania: 2NHG-TAPW-AY2Q-0KRA Slovakia: 2NHG-TAPW-AY2Q-0KRA Slovenia: 2NHG-TAPW-AY2Q-0KRA Spain: 2NHG-TAPW-AY2Q-0KRA Sweden: 2NHG-TAPW-AY2Q-0KRA

Hazard pictograms

Signal word Hazard statements



H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
Precautionary statements	
Prevention	
P210 P102	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep out of reach of children.
Response	
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
Storage	Not applicable.
Disposal	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Supplemental label information	EUH208 - Contains Ethyl methylphenylglycidate, Oils, orange, sweet, terpene-free, delta-Damascone. May produce an allergic reaction.
2.3. Other hazards	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

## **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

### **General information**

Chemical name	%	CAS-No. / EC No.	<b>REACH Registration No</b>	. Index No.	Notes
Ethanol	60 - 70	64-17-5 200-578-6	-	603-002-00-5	
Classification	Flam. Liq.	2;H225, Eye Irrit. 2;H	319		
(2,2-Dimethyl-1,3-dioxolan-4-yl)metha nol	3 - 5	100-79-8 202-888-7	-	-	
Classification	Eye Irrit. 2	;H319			
benzyl benzoate	1 - 3	120-51-4 204-402-9	01-2119976371-33	607-085-00-9	
Classification	Acute Tox Chronic 2;	, ,	g/kg bw), Aquatic Acute 1	H400, Aquatic	
Ethyl methylphenylglycidate	≤ 1	77-83-8 201-061-8	-	-	
Classification	Skin Sens	. 1B;H317, Aquatic C	hronic 2;H411		
Oils, orange, sweet, terpene-free	≤ 0,3	68606-94-0 614-649-8	-	-	
Classification		3;H226, Skin Irrit. 2;F sp. Tox. 1;H304, Aqu	1315, Eye Irrit. 2;H319, Ski atic Chronic 2;H411	n Sens.	
delta-Damascone	≤ 0,1	57378-68-4 260-709-8	-	-	
Classification			g/kg bw), Skin Irrit. 2;H315 , Aquatic Chronic 1;H410	5, Skin Sens.	
Other components below reportable levels	25.32				

### List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** The full text for all H-statements is displayed in section 16.

### **SECTION 4: First aid measures**

### **General information**

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

#### 4.1. Description of first aid measures Inhalation Mov

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
4.2. Most important symptoms and effects, both acute and delayed	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
SECTION 5: Firefighting m	leasures
General fire hazards	Highly flammable liquid and vapour.
5.1. Extinguishing media Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special fire fighting procedures	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
SECTION 6: Accidental rel	ease measures
6.1. Personal precautions, protection	ctive equipment and emergency procedures
For non-emergency personnel	Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
For emergency responders	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.
6.2. Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent entry into waterways, sewer, basements or confined areas.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use.
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.
SECTION 7: Handling and	storage
7.1. Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust
	ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
7.2. Conditions for safe	Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using

7.2. Conditions for safe	Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using
storage, including any	common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store
incompatibilities	in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).
7.3. Specific end use(s)	Observe industrial sector guidance on best practices.

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

### **Occupational exposure limits**

# Austria. MAK List, OEL Ordinance (GwV), BGBI. II, no. 184/2001

Components	Туре	Value
Ethanol (CAS 64-17-5)	Ceiling	3800 mg/m3
		2000 ppm
	MAK	1900 mg/m3
		1000 ppm
Belgium. Exposure Limit Values		
Components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1907 mg/m3
		1000 ppm
Bulgaria. OELs. Regulation No 13 on	protection of workers agai	inst risks of exposure to chemical agents at work
Components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1000 mg/m3
Croatia. Dangerous Substance Expos Components	sure Limit Values in the Wo Type	orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09 Value
Ethanol (CAS 64-17-5)	MAC	1900 mg/m3
		1000 ppm
Czech Republic. OELs. Government I	Decree 361	
Components	Туре	Value
Ethanol (CAS 64-17-5)	Ceiling	3000 mg/m3
	TWA	1000 mg/m3
Denmark. Exposure Limit Values		
Components	Туре	Value
Ethanol (CAS 64-17-5)	TLV	1900 mg/m3
		1000 ppm
Estonia. OELs. Occupational Exposu	re Limits of Hazardous Sul	bstances (Regulation No. 105/2001, Annex), as amended
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3
		1000 ppm
	TWA	1000 mg/m3
		500 ppm
Finland. Workplace Exposure Limits		
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	2500 mg/m3
		1300 ppm
	TWA	1900 mg/m3
		1000 ppm
France. Threshold Limit Values (VLEI Components	P) for Occupational Exposi Type	ure to Chemicals in France, INRS ED 984 Value
Ethanol (CAS 64-17-5)	VLE	9500 mg/m3
Regulatory status: Indicative lim	nit (VL)	
		5000 ppm
Regulatory status: Indicative lin	nit (VL)	
		1000

Indicative limit (VL)

Indicative limit (VL)

**Regulatory status:** 

**Regulatory status:** 

VME

1900 mg/m3

1000 ppm

in the Work Area (DFG) Components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	380 mg/m3
		200 ppm
Cormany TRGS 900 Limit Valu	es in the Ambient Air at the Wo	
components	Type	Value
thanol (CAS 64-17-5)	AGW	380 mg/m3
		200 ppm
reece. OELs (Decree No. 90/19	(bobnome ac . PP	
components	Туре	Value
thanol (CAS 64-17-5)	TWA	1900 mg/m3
		1000 ppm
ungary, OELs, Joint Decree or	Chemical Safety of Workplace	s
components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	3800 mg/m3
·	TWA	1900 mg/m3
celand, OFLs, Regulation 154/1	999 on occupational exposure	limits
Components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3
		1000 ppm
eland. Occupational Exposure	Limits	
components	Туре	Value
thanol (CAS 64-17-5)	STEL	1000 ppm
aly. Occupational Exposure Li	nits	
components	Туре	Value
thanol (CAS 64-17-5)	STEL	1000 ppm
atvia OFLs Occupational exp	osure limit values of chemical s	substances in work environment
components	Туре	Value
thanol (CAS 64-17-5)	TWA	1000 mg/m3
ithuania_OELs_Limit Values f	or Chemical Substances, Gene	ral Requirements
omponents	Туре	Value
thanol (CAS 64-17-5)	STEL	1900 mg/m3
		1000 ppm
	TWA	1000 mg/m3
		500 ppm
letherlands. OELs (binding)		
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3
	TWA	260 mg/m3
Jonway Administrativo Norma (		·
components	or Contaminants in the Workpl Type	ace Value
	TLV	950 mg/m3
	v	500 ppm
		on 6 June 2014 on the maximum permissible work environment, Journal of Laws 2014, item 817
Components	Туре	Value

Stream is an analysis of the series of the interval of the interval of the series of the se	Components	occupational exposure to chemica Type	Value
Components         Type         Value           Ethanol (CAS 64-17-5)         STEL         9500 mg/m3 5000 ppm           TWA         1900 mg/m3 1000 ppm           Bloavakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents components         Type           Bloavakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents components         1900 mg/m3 1000 ppm           Bloavakia. OELs. Regulation Sconcerning protection of workers against risks due to exposure to chemicals while we official Gazette of the Republic of Slovenia)         960 mg/m3 500 ppm           Stovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while we official Gazette of the Republic of Slovenia)         960 mg/m3 500 ppm           Stovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while we official Gazette of the Republic of Slovenia)         960 mg/m3 500 ppm           Stovenia. OELs. Regulations Exposure Limits         Type         Value           Stanol (CAS 64-17-5)         TWA         960 mg/m3 1000 ppm           Stanol (CAS 64-17-5)         STEL         1910 mg/m3 1000 ppm           Stanol (CAS 64-17-5)         STEL         1900 mg/m3 1000 ppm           Stanol (CAS 64-17-5)         STEL         1900 mg/m3 1000 ppm           Stanol (CAS 64-17-5)         STEL         1900 mg/m3 1000 ppm <tr< th=""><th>Ethanol (CAS 64-17-5)</th><th>TWA</th><th>1000 ppm</th></tr<>	Ethanol (CAS 64-17-5)	TWA	1000 ppm
Sthanol (CAS 64-17-5) STEL 9500 mg/m3 5000 ppm TWA 1900 mg/m3 1000 ppm Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents 50mponents Type Value Ethanol (CAS 64-17-5) STEL 1920 mg/m3 1000 ppm TWA 960 mg/m3 500 ppm Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while we Official Gazette of the Republic of Slovenia) 20mponents Type Value Ethanol (CAS 64-17-5) TWA 960 mg/m3 500 ppm Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while we Official Gazette of the Republic of Slovenia) 20mponents Type Value Ethanol (CAS 64-17-5) TWA 960 mg/m3 500 ppm Saveden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) 50mponents Type Value Ethanol (CAS 64-17-5) STEL 1910 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm TWA 1000 mg/m3 500 ppm TWA 1000 mg/m3 500 ppm TWA 500 ppm TWA 500 ppm TWA 500 ppm TWA 1000 mg/m3 500 ppm TWA 1000 ppm TWA 1000 mg/m3 500 ppm TWA 1000 mg/m3 500 ppm TWA 1000 mg/m3 500 ppm	Romania. OELs. Protectio Components	-	•
Store is a straight of the second			9500 mg/m3
TWA     1900 mg/m3 1000 ppm       Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents components     Type       Standal (CAS 64-17-5)     STEL     1920 mg/m3 1000 ppm       TWA     6800 mg/m3 500 ppm     500 ppm       Slovania. OELs. Regulations concerning protection of workers against risks     ue to exposure to chemicals while we Official Gazents of the Republic of Slovania)       Somponents     Type     Value       Ethanol (CAS 64-17-5)     TWA     960 mg/m3 500 ppm       Spain. Occupational Exposure Limits     Type     Value       Standard (CAS 64-17-5)     STEL     1910 mg/m3 1000 ppm       Spain. Occupational Exposure Limits     Type     Value       Standard (CAS 64-17-5)     STEL     1910 mg/m3 1000 ppm       Standard (CAS 64-17-5)     STEL     1910 mg/m3 1000 ppm       Standard (CAS 64-17-5)     STEL     1900 mg/m3 1000 ppm       Standard (CAS 64-17-5)     STEL     1920 mg/m3 1000 ppm       Standard (CAS 64-17-5)     STEL     1920 mg/m3 1000 ppm       Standard (CAS 64-17-5)     TVA     1920 mg/m3 1000 ppm       Standard (CAS 64-17-5)		0122	-
1000 pm       1000 pm       Value       Value       Value       Value       1000 ppm       TWA     960 mg/m3       500 ppm       Value       Components       TWA     960 mg/m3       Somponents       TWA     960 mg/m3       Somponents       TWA     960 mg/m3       Somponents       Type       Value       Components       Type       Value       Components       Type       Value       Components       Type       Value       Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2">Colspan="2"       Colspan="2" </td <td></td> <td>Τινία</td> <td></td>		Τινία	
Novakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents         Somponents       Type       Value         Sthanol (CAS 64-17-5)       STEL       1920 mg/m3         TWA       960 mg/m3       500 ppm         Stovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while were of the Republic of Slovenia)       7000 ppm         Components       Type       Value         Status of the Republic of Slovenia)       500 ppm         Somponents       Type       Value         Status of the Republic of Slovenia)       500 ppm         Somponents       Type       Value         Status of the Republic of Slovenia)       500 ppm         Somponents       Type       Value         Status of the Republic of Slovenia)       500 ppm         Somponents       Type       Value         Status of the Republic of Slovenia)       500 ppm         Somponents       Type       Value         Status of the Republic of Slovenia)       1000 ppm         Somponents       Type       Value         Status of the Republic of Slovenia)       1000 ppm         Somponents       Type       Value         Status of the Republic of Slovenia)       5			C C
Components         Type         Value           Ethanol (CAS 64-17-5)         STEL         1200 mg/m3           Iteration of the Republic of Slovenia         500 ppm           Stovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while workers against risks due to exposure to chemicals while workers against risks due to exposure to chemicals while workers against risks due to exposure to chemicals while workers against risks due to exposure to chemicals while workers against risks due to exposure to chemicals while workers against risks due to exposure to chemicals while workers against risks due to exposure to chemicals while workers against risks due to exposure to chemicals while workers against risks due to exposure to chemicals while workers against risks due to exposure to chemicals while workers against risks due to exposure to chemicals while workers against risks due to exposure to chemicals while workers against risks due to exposure to chemicals while workers against risks due to exposure to chemicals while workers against risks due to exposure to chemicals while workers against risks due to exposure to chemicals while workers against risks due to exposure to chemicals while workers against risks due to exposure to the top of the tage of the Republic of Slovenia           Stomponents         Type         Value           Ethanol (CAS 64-17-5)         STEL         1900 mg/m3           Stotzeriand. SUVA Grenzwerte am Arbeitsplatz         1000 ppm           Somponents         Type         Value           Stream of (CAS 64-17-5)         STEL         1920 mg/m3           Stop ppm </td <td></td> <td>No. 000/0007</td> <td></td>		No. 000/0007	
1000 ppm       TWA       960 mg/m3       500 ppm       Solvenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while word official Gazette of the Republic of Slovenia)       Somponents       Type       Value       Statual (CAS 64-17-5)       STEL     1910 mg/m3       1000 ppm       Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015.7)       Components       Type       Value       Ethanol (CAS 64-17-5)       STEL     1900 mg/m3       1000 ppm       TWA     1000 ppm       Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015.7)       Components       Type     Value       Ethanol (CAS 64-17-5)     STEL     1900 mg/m3       Switzerland. SUVA Grenzwerte am Arbeitsplatz       Components     Type     Value       Ethanol (CAS 64-17-5)     STEL     1920 mg/m3       Solopponents       Type     Value       Components     Type <t< td=""><td>Components</td><td></td><td></td></t<>	Components		
TWA     960 mg/m3 500 ppm       Stovenia, OELs, Regulations concerning protection of workers against risks due to exposure to chemicals while we Official Gazetto of the Republic of Slovenia)     Value       Somponents     Type     Value       Ethanol (CAS 64-17-5)     TWA     960 mg/m3 500 ppm       Spain. Occupational Exposure Limits Components     Type     Value       Ethanol (CAS 64-17-5)     STEL     1910 mg/m3 1000 ppm       Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Components     Type       Weden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Components     Type       Walue     1000 ppm       Ethanol (CAS 64-17-5)     STEL     1900 mg/m3 1000 ppm       TWA     1000 ppm     1000 ppm       TWA     960 mg/m3 500 ppm     1000 ppm       Switzerland. SUVA Grenzwerte am Arbeitsplatz components     Type     Value       Ethanol (CAS 64-17-5)     STEL     1920 mg/m3 1000 ppm       Switzerland. SUVA Grenzwerte tam Arbeitsplatz     1000 ppm       TWA     960 mg/m3 1000 ppm     1000 ppm       TWA     1000 ppm     1000 ppm       Ethanol (CAS 64-17-5)     TWA	Ethanol (CAS 64-17-5)	STEL	1920 mg/m3
Soveria. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while we Official Gazette of the Republic of Slovenia) Somponents Type Value Ethanol (CAS 64-17-5) TWA 960 mg/m3 Spain. Occupational Exposure Limits Components Type Value Ethanol (CAS 64-17-5) STEL 1910 mg/m3 1000 ppm Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Components Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm TWA 960 mg/m3 500 ppm TWA 960 mg/m3 500 ppm TWA 960 mg/m3 1000 ppm TWA 1000 ppm TWA 960 mg/m3 1000 ppm TWA 1000 ppm TWA 960 mg/m3 1000 ppm TWA 1000 ppm			1000 ppm
Novenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while work Official Gazette of the Republic of Slovenia) Components Type Value Ethanol (CAS 64-17-5) TWA 600 mg/m3 500 ppm Seveden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm TWA 1000 ppm TWA 1000 mg/m3 500 ppm TWA 1000 ppm TWA 1000 mg/m3 500 ppm TWA 1000 mg/m3 1000 ppm TWA 100		TWA	960 mg/m3
Official Gazette of the Republic of Slovēnia)       Components     Type     Value       Ethanol (CAS 64-17-5)     TWA     960 mg/m3       Spain. Occupational Exposure Limits     500 ppm       Spain. Occupational Exposure Limits     Type     Value       Stanol (CAS 64-17-5)     STEL     1910 mg/m3       Stanol (CAS 64-17-5)     STEL     1900 mg/m3       Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)     Yupe       Somponents     Type     Value       Ethanol (CAS 64-17-5)     STEL     1900 mg/m3       Switzerland. SUVA Grenzwerte am Arbeitsplatz     500 ppm       Somponents     Type     Value       Ethanol (CAS 64-17-5)     STEL     1920 mg/m3       Switzerland. SUVA Grenzwerte am Arbeitsplatz     500 ppm       Somponents     Type     Value       Ethanol (CAS 64-17-5)     STEL     1920 mg/m3       Stanol (CAS 64-17-5)     STEL     1920 mg/m3       Stanol (CAS 64-17-5)     Type     Value       Stanol (CAS 64-17-5)     Type     Val			500 ppm
Components         Type         Value           Ethanol (CAS 64-17-5)         TWA         960 mg/m3 500 ppm           Spain. Occupational Exposure Limits         Type         Value           Ethanol (CAS 64-17-5)         STEL         1910 mg/m3 1000 ppm           Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)         Value           Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)         Value           Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)         Value           Stendor (CAS 64-17-5)         STEL         1900 mg/m3 1000 ppm           Ethanol (CAS 64-17-5)         STEL         1900 mg/m3 500 ppm           Switzerland. SUVA Grenzwerte am Arbeitsplatz         500 ppm           Components         Type         Value           Stendor (CAS 64-17-5)         STEL         1920 mg/m3 500 ppm           Switzerland. SUVA Grenzwerte Limits (WELs)         500 ppm         1000 ppm           TWA         1920 mg/m3 1000 ppm         500 ppm           JK. EH40 Workplace Exposure Limits (WELs)         500 ppm         1000 ppm           Camponents         Type         Value           Stendor (CAS 64-17-5)         Type         Value           Stendor (CAS 64-17			ers against risks due to exposure to chemicals while work
Ethanol (CAS 64-17-5)     TWA     960 mg/m3       Spain. Occupational Exposure Limits     500 ppm       Spain. Occupational Exposure Limits     1910 mg/m3       Components     Type     Value       Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)     Value       Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)     Value       Ethanol (CAS 64-17-5)     STEL     1900 mg/m3       Switzerland. SUVA Grenzwerte am Arbeitsplatz     1000 ppm       Switzerland. SUVA Grenzwerte am Arbeitsplatz     1000 ppm       Somponents     Type     Value       Ethanol (CAS 64-17-5)     STEL     1920 mg/m3       Switzerland. SUVA Grenzwerte am Arbeitsplatz     1000 ppm       Somponents     Type     Value       Ethanol (CAS 64-17-5)     STEL     1920 mg/m3       Sthanol (CAS 64-17-5)     TWA     960 mg/m3       Stanol (CAS 64-17-5)     TWA     1920 mg/m3       Somponents     Type     Value       Ethanol (CAS 64-17-5)     TWA     1920 mg/m3       Stanol (CAS 64-17-5)     TWA     1920 mg/m3	(Official Gazette of the Re Components		Value
Spain. Occupational Exposure Limits Components         Type         Value           Ethanol (CAS 64-17-5)         STEL         1910 mg/m3 1000 ppm           Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Components         Type           Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Components         Type           Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Components         1900 mg/m3 1000 ppm           Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Components         1900 mg/m3 1000 ppm           Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (DFS 2015:7) Sweden. OELs. Value         1000 ppm           Sweden. OELs. Work Environment Authority (MELS) Components         Type         Value           Sweden. OCAS 64-17-5)         STEL         1920 mg/m3 1000 ppm         1000 ppm           TWA         960 mg/m3 500 ppm         1000 ppm         1000 ppm           KE. EH40 Workplace Exposure Limits (WELs) Components         Type         Value           Stanol (CAS 64-17-5)         TWA         1920 mg/m3 1000 ppm           Igical limit values         No biological exposure limits noted for the ingredient(s).         Immended monitoring procedures.           Isoter on	Ethanol (CAS 64-17-5)		960 mg/m3
Spain. Occupational Exposure Limits         Type         Value           Ethanol (CAS 64-17-5)         STEL         1910 mg/m3 1000 ppm           Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Somponents         Type         Value           Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Somponents         Type         Value           Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Somponents         1900 mg/m3 1000 ppm           Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Somponents         1900 mg/m3 1000 ppm           Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limits (TVA Somponents         1900 mg/m3 1000 ppm           Sweden. SUVA Grenzwerte am Arbeitsplatz Somponents         Type         Value           Sweden. OCAS 64-17-5)         STEL         1920 mg/m3 1000 ppm           TWA         960 mg/m3 500 ppm         500 ppm           JK. EH40 Workplace Exposure Limits (WELS) Components         Type         Value           Sthanol (CAS 64-17-5)         TWA         1920 mg/m3 1000 ppm           Igical limit values edures         No biological exposure limits noted for the ingredient(s).           Immended monitoring red no effect levels et ef no effect levels sure guidelines         Not available.           Ustere	· · · · · · · · · · · · · · · · · · ·		-
Components     Type     Value       Ethanol (CAS 64-17-5)     STEL     1910 mg/m3 1000 ppm       Sweden, OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Components     Type     Value       Stel     1900 mg/m3 1000 ppm     1000 pgm       Ethanol (CAS 64-17-5)     STEL     1900 mg/m3 500 ppm       Switzerland. SUVA Grenzwerte am Arbeitsplatz     1000 pgm       Components     Type     Value       Switzerland. SUVA Grenzwerte am Arbeitsplatz     1000 ppm       Switzerland. SUVA Grenzwerte am Arbeitsplatz     1000 pgm       Switzerland. SUVA Grenzwerte am Arbeitsplatz     1000 ppm       Switzerland. SUVA Grenzwerte am Arbeitsplatz     1000 ppm       Switzerland. SUVA Grenzwerte am Arbeitsplatz     1000 pgm       Switzerland. CAS 64-17-5)     STEL     1920 mg/m3 1000 ppm       TWA     960 mg/m3 500 ppm     500 ppm       JK. EH40 Workplace Exposure Limits (WELs)     Value       Components     Type       Value     1000 ppm       Stanol (CAS 64-17-5)     TWA     1920 mg/m3 1000 ppm       Igical limit values     No biological exposure limits noted for the ingredient(s).       Immeded monitoring Burges     Follow standard monitoring procedures.       red no effect levels     Not available.       Ls)     Not available.	Spain Occupational Expo	suro Limite	
1000 ppm       Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) Value       Somponents       Type       Value       Ethanol (CAS 64-17-5)       STEL     1900 mg/m3 1000 ppm       TWA     1000 mg/m3 500 ppm       Switzerland. SUVA Grenzwerte am Arbeitsplatz       Components     Type       Value       Ethanol (CAS 64-17-5)     STEL     1920 mg/m3 1000 ppm       SWIZERIANDI (CAS 64-17-5)     STEL     1920 mg/m3 1000 ppm       JK. EH40 Workplace Exposure Limits (WELS)       Components     Type       Value       Switzeriandle (CAS 64-17-5)     TWA     1920 mg/m3 1000 ppm       JK. EH40 Workplace Exposure Limits (WELS)       Components     Type       Value       Ethanol (CAS 64-17-5)     TWA     1920 mg/m3 1000 ppm       Igical limit values     No biological exposure limits noted for the ingredient(s).       Follow standard monitoring procedures.       etd no effect levels     Not available.       Limit of IPECS)       sure guidelines       Sti	Components		Value
Value           Value           Value           Ethanol (CAS 64-17-5)         STEL         1900 mg/m3           1000 ppm         1000 mg/m3         500 ppm           Value           Switzerland. SUVA Grenzwerte am Arbeitsplatz           Components         Type         Value           Switzerland. SUVA Grenzwerte am Arbeitsplatz         Value         1000 ppm           Type         Value           Ethanol (CAS 64-17-5)         STEL         1920 mg/m3           1000 ppm         TWA         960 mg/m3           1000 ppm         TWA         960 mg/m3           1000 ppm         TWA         900 ppm           KK. EH40 Workplace Exposure Limits (WELs)         Value         1000 ppm           Components         Type         Value         1000 ppm           Ethanol (CAS 64-17-5)         TWA         1920 mg/m3         1000 ppm           Iggical limit values         No biological exposure limits noted for the ingredium         1000 ppm           Iggical limit values         Not available.         Immended monitoring         Immended monitoring           red no effect levels         Not available.         Immended monitoring (PNECs)         Imm	Ethanol (CAS 64-17-5)	STEL	1910 mg/m3
Components     Type     Value       Ethanol (CAS 64-17-5)     STEL     1900 mg/m3       TWA     1000 ppm       TWA     1000 mg/m3       Soutzerland. SUVA Grenzwerte am Arbeitsplatz     500 ppm       Soutzerland. SUVA Grenzwerte am Arbeitsplatz     Value       Components     Type       State     1920 mg/m3       State     1000 ppm       TWA     960 mg/m3       Soutzerland. CAS 64-17-5)     STEL       TWA     960 mg/m3       Soutzerland. CAS 64-17-5)     TWA       State     Type       Value     TWA       TWA     960 mg/m3       Soutzerland. CAS 64-17-5)     TWA       State     Type       Value     TWA       State     Soutzerland       State     Type       Value     TWA       Soutzerland. CAS 64-17-5)     TWA       State     Type       Value     TWA       State     Soutzerland       State     Type       Value     Soutzerland       State     Soutzerland       State     Type       Value     Soutzerland       State     Soutzerland       State     Soutzerland       State			1000 ppm
TWA     1000 ppm       Switzerland. SUVA Grenzwerte am Arbeitsplatz     500 ppm       Components     Type     Value       Ethanol (CAS 64-17-5)     STEL     1920 mg/m3       Ethanol (CAS 64-17-5)     STEL     1900 ppm       TWA     960 mg/m3     500 ppm       JUX. EH40 Workplace Exposure Limits (WELs)     TWA     960 mg/m3       Components     Type     Value       Ethanol (CAS 64-17-5)     TWA     1920 mg/m3       Streamended monitoring     No biological exposure limits noted for the ingredient(s).     1000 ppm       Ethanol (CAS 64-17-5)     TWA     1920 mg/m3       Indegred monitoring     Follow standard monitoring procedures.     1000 ppm       Edures     Not available.	Sweden. OELs. Work Envi Components		
TWA     1000 mg/m3 500 ppm       Switzerland. SUVA Grenzwerte am Arbeitsplatz components     Type       Stell     1920 mg/m3 1000 ppm       Ethanol (CAS 64-17-5)     STEL     1920 mg/m3 1000 ppm       TWA     960 mg/m3 500 ppm       JK. EH40 Workplace Exposure Limits (WELs) Components     TWA     960 mg/m3 1000 ppm       JK. EH40 Workplace Exposure Limits (WELs)     TWA     1920 mg/m3 1000 ppm       Components     TWA     1920 mg/m3 1000 ppm       Ethanol (CAS 64-17-5)     No biological exposure limits noted for the ingredient(s).       Follow standard monitoring procedures.     Follow standard monitoring procedures.       Ethanol (CAS 64-17-5)     Not available.	Ethanol (CAS 64-17-5)	STEL	1900 mg/m3
Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Ethanol (CAS 64-17-5) STEL 1920 mg/m3 1000 ppm TWA 960 mg/m3 500 ppm VX. EH40 Workplace Exposure Limits (WELs) Components Type Value Ethanol (CAS 64-17-5) TWA 1920 mg/m3 1000 ppm Ethanol (CAS 64-17-5) TWA 1920 mg/m3 1000 ppm Ethanol (CAS 64-17-5) Not available. Ethanol (CAS 64-17-5) Not availa			1000 ppm
Switzerland. SUVA Grenzwerte am Arbeitsplatz Components         Type         Value           Ethanol (CAS 64-17-5)         STEL         1920 mg/m3 1000 ppm           TVVA         960 mg/m3 500 ppm           JK. EH40 Workplace Exposure Limits (WELs) Components         Type           ZMARCH (CAS 64-17-5)         TWA           Sthanol (CAS 64-17-5)         TWA           Stanol (CAS 64-17-5)         TWA           Stanol (CAS 64-17-5)         No biological exposure limits noted for the ingredient(s).           Stanol (CAS 64-17-5)         Not available.		TWA	1000 mg/m3
Components       Type       Value         Ethanol (CAS 64-17-5)       STEL       1920 mg/m3         1000 ppm       TWA       960 mg/m3         500 ppm       500 ppm         JK. EH40 Workplace Exposure Limits (WELs)       Value         Components       Type         JK. EH40 Workplace Exposure Limits (WELs)       Value         Components       Type         Value       Value         Ethanol (CAS 64-17-5)       TWA         Immediation of CAS 64-17-5)       TWA         Immediation of CAS 64-17-5)       TWA         Immediation of CAS 64-17-5)       No biological exposure limits noted for the ingredimestry indicestry inditandef         Indit			500 ppm
Components       Type       Value         Ethanol (CAS 64-17-5)       STEL       1920 mg/m3         1000 ppm       TWA       960 mg/m3         500 ppm       500 ppm         JK. EH40 Workplace Exposure Limits (WELs)       Value         Components       Type         JK. EH40 Workplace Exposure Limits (WELs)       Value         Components       Type         Value       Value         Ethanol (CAS 64-17-5)       TWA         Immediation of CAS 64-17-5)       TWA         Immediation of CAS 64-17-5)       TWA         Immediation of CAS 64-17-5)       No biological exposure limits noted for the ingredimestry indicestry inditandef         Indit	Switzerland, SUVA Grenzy	werte am Arbeitsplatz	
TWA       1000 ppm         960 mg/m3       500 ppm         JK. EH40 Workplace Exposure Limits (WELs)       Value         Components       Type         Zthanol (CAS 64-17-5)       TWA         TWA       1920 mg/m3         1000 ppm         regical limit values       No biological exposure limits noted for the ingredient(s).         mmended monitoring edures       Follow standard monitoring procedures.         edures       Not available.         Ls)       Not available.         isted no effect levels entrations (PNECs)       Not available.         sure guidelines       Not available.         Vetherlands OELs (binding): Skin designation       Skin designation	Components	-	Value
TWA     960 mg/m3 500 ppm       DK. EH40 Workplace Exposure Limits (WELs) Components     Type       Value       Ethanol (CAS 64-17-5)     TWA       1920 mg/m3 1000 ppm       regical limit values     No biological exposure limits noted for the ingredient(s).       regical limit values     No biological exposure limits noted for the ingredient(s).       regical limit values     Not available.       red no effect levels Ls)     Not available.       red no effect no effect entrations (PNECs)     Not available.       resure guidelines     Not available.	Ethanol (CAS 64-17-5)	STEL	1920 mg/m3
JK. EH40 Workplace Exposure Limits (WELs)       500 ppm         Components       Type       Value         Ethanol (CAS 64-17-5)       TWA       1920 mg/m3 1000 ppm         egical limit values       No biological exposure limits noted for the ingredient(s).       Immediate monitoring procedures.         edures       Follow standard monitoring procedures.       Immediate monitoring procedures.         edures       Not available.       Immediate monitoring procedures.         icted no effect levels       Not available.       Immediate monitoring procedures.         icted no effect       Not available.       Immediate monitoring procedures.         istre guidelines       Immediate monitoring procedures.       Immediate monitoring procedures. <td></td> <td></td> <td>1000 ppm</td>			1000 ppm
M. EH40 Workplace Exposure Limits (WELs)         Components       Type       Value         Ethanol (CAS 64-17-5)       TWA       1920 mg/m3         gical limit values       No biological exposure limits noted for the ingredient(s).       1000 ppm         regical limit values       No biological exposure limits noted for the ingredient(s).       Follow standard monitoring procedures.         red no effect levels       Not available.       Not available.         LLs)       Not available.       Standard monitoring procedures.         sure guidelines       Not available.       Standard monitoring procedures.		TWA	960 mg/m3
ComponentsTypeValueEthanol (CAS 64-17-5)TWA1920 mg/m3 1000 ppmregical limit valuesNo biological exposure limits noted for the ingredient(s).regical limit valuesNo biological exposure limits noted for the ingredient(s).regical limit valuesFollow standard monitoring procedures.red no effect levelsNot available.ricted no effect entrations (PNECs)Not available.sure guidelinesNot available.retherlands OELs (binding): Skin designation			500 ppm
Ethanol (CAS 64-17-5)       TWA       1920 mg/m3         function of the ingredient (s).       1000 ppm         regical limit values       No biological exposure limits noted for the ingredient(s).         remmended monitoring       Follow standard monitoring procedures.         red no effect levels       Not available.         icted no effect       Not available.         entrations (PNECs)       Not available.         sure guidelines       Skin designation			
non-section       No biological exposure limits noted for the ingredient(s).         non-mended monitoring edures       Follow standard monitoring procedures.         edures       Not available.         iLs)       Not available.         icted no effect levels       Not available.         entrations (PNECs)       Not available.         isure guidelines       Skin designation	Components	Туре	Value
ogical limit values       No biological exposure limits noted for the ingredient(s).         immended monitoring edures       Follow standard monitoring procedures.         red no effect levels       Not available.         icted no effect entrations (PNECs)       Not available.         isure guidelines       Not available.         Netherlands OELs (binding): Skin designation       Skin designation	Ethanol (CAS 64-17-5)	TWA	C C
mmended monitoring       Follow standard monitoring procedures.         edures       Follow standard monitoring procedures.         red no effect levels       Not available.         icted no effect       Not available.         entrations (PNECs)       Not available.         isure guidelines       Skin designation			1000 ppm
edures ved no effect levels Not available. Ls) icted no effect Not available. entrations (PNECs) sure guidelines Netherlands OELs (binding): Skin designation	ogical limit values	No biological exposure limits not	ed for the ingredient(s).
red no effect levels       Not available.         iLs)       Not available.         icted no effect       Not available.         entrations (PNECs)       Image: Comparison of the second	ommended monitoring cedures	Follow standard monitoring proce	edures.
icted no effect Not available. entrations (PNECs) sure guidelines Netherlands OELs (binding): Skin designation	ived no effect levels ELs)	Not available.	
Netherlands OELs (binding): Skin designation	dicted no effect centrations (PNECs)	Not available.	
	osure guidelines		
Emanor (CAS 04-17-5) Can be absorbed through the skin.			an be absorbed through the elite
	Ethanol (CAS 64-17-5) Exposure controls	Ĺ	an be absorbed through the SKIN.

Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.
Individual protection measures,	such as personal protective equipment
General information	Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
- Hand protection	Wear appropriate chemical resistant gloves.
- Other	Wear suitable protective clothing.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

SECTION 9: Physical and chemical properties		
9.1. Information on basic physica	al and chemical properties	
Physical state	Liquid.	
Form	Liquid.	
Colour	Not available.	
Odour	Not available.	
Melting point/freezing point	-114 °C (-173,2 °F) estimated	
Boiling point or initial boiling point and boiling range	78,4 °C (173,12 °F) estimated	
Flammability	Not applicable.	
Flash point	13 °C (55,4 °F) estimated	
Auto-ignition temperature	365 °C (689 °F) estimated	
Decomposition temperature	Not available.	
рН	Not available.	
Kinematic viscosity	Not available.	
Solubility		
Solubility (water)	Not available.	
Partition coefficient (n-octanol/water) (log value)	Not available.	
Vapour pressure	33,342076 hPa estimated	
Density and/or relative density		
Density	0,846 g/cm3 estimated	
Vapour density	Not available.	
Particle characteristics	Not available.	
9.2. Other information		
9.2.1. Information with regard to physical hazard classes	No relevant additional information available.	
9.2.2. Other safety characteristics		
Percent volatile	91,59 % estimated	
Specific gravity	0,84647 estimated	
VOC	68,45 % estimated	
SECTION 10. Stability and	reactivity	

# **SECTION 10: Stability and reactivity**

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.

Material name: YC ICED BERRY LEMONADE REED DIFFUSER REFILL 1745740E 1745740E Version #: 01 Issue date: 28-June-2023

10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

# **SECTION 11: Toxicological information**

Occupational exposure to the substance or mixture may cause adverse effects. **General information** Information on likely routes of exposure Inhalation May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation may be harmful. Skin contact May cause an allergic skin reaction. Eye contact Causes serious eve irritation. Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure. Symptoms Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 No data available. Acute toxicity Due to partial or complete lack of data the classification is not possible. Skin corrosion/irritation Serious eye damage/eye Causes serious eve irritation. irritation **Respiratory sensitisation** Due to partial or complete lack of data the classification is not possible. Skin sensitisation Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible. Germ cell mutagenicity Carcinogenicity Due to partial or complete lack of data the classification is not possible. Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended) Not listed. **Reproductive toxicity** Due to partial or complete lack of data the classification is not possible. Specific target organ toxicity -Due to partial or complete lack of data the classification is not possible. single exposure Specific target organ toxicity -Due to partial or complete lack of data the classification is not possible. repeated exposure Aspiration hazard Due to partial or complete lack of data the classification is not possible. Mixture versus substance No information available. information 11.2. Information on other hazards Endocrine disrupting This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No properties 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight. Other information May cause allergic respiratory and skin reactions. **SECTION 12: Ecological information** 12.1. Toxicity Based on available data, the classification criteria are not met for hazardous to the aguatic environment

Components		Species	Test Results
(2,2-Dimethyl-1,3-dioxolan-4	1-yl)methanol (CA	S 100-79-8)	
Aquatic			
Acute			
Fish	LC50	Fathead minnow (Pimephales prom	nelas) 15200 - 18300 mg/l, 96 hours
Ethanol (CAS 64-17-5)			
Aquatic			
Acute			
Crustacea	EC50	Water flea (Daphnia magna)	7,7 - 11,2 mg/l, 48 hours

Components	Sp	ecies	Test Results
Fish		inbow trout,donaldson trout ncorhynchus mykiss)	42 mg/l, 4 days
12.2. Persistence and degradability	No data is availabl	e on the degradability of any ingre	edients in the mixture.
12.3. Bioaccumulative potentia	l		
Partition coefficient n-octanol/water (log Kow)			
(2,2-Dimethyl-1,3-dioxolan-4	-yl)methanol	0,3	
benzyl benzoate		3,97	
delta-Damascone		3,4	
		4,2	
Ethanol		-0,31	
Ethyl methylphenylglycidate		2,8	
<b>Bioconcentration factor (BCF)</b>	Not available.		
12.4. Mobility in soil	No data available.		
12.5. Results of PBT and vPvB assessment	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.		
12.6. Endocrine disrupting properties	This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.		
12.7. Other adverse effects	The product conta potential.	ins volatile organic compounds w	which have a photochemical ozone creation
12.8. Additional information			
Estonia Dangerous substa	inces in soil Data		
benzyl benzoate (CAS	120-51-4)	Chemical pesticides 0,5 mg/kg	s (As the total sum of the active substances)
			s (As the total sum of the active substances) 20
			s (As the total sum of the active substances) 5

Ethanol (	(CAS	64-17-5)
		0 - 17 - 0)

mg/kg Chemical pesticides (As the total sum of the active substances) 0,5 mg/kg

Chemical pesticides (As the total sum of the active substances) 20 mg/kg

Chemical pesticides (As the total sum of the active substances) 5 mg/kg

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

# **SECTION 14: Transport information**

ADR

DR	
14.1. UN number	UN1993
14.2. UN proper shipping	FLAMMABLE LIQUID, N.O.S. (vapour pressure at 50 °C more than 110 kPa) (Ethanol,
name	(2,2-Dimethyl-1,3-dioxolan-4-yl)methanol)
14.3. Transport hazard class	(es)
Class	3
Subsidiary risk	-
Label(s)	3
Hazard No. (ADR)	33
Tunnel restriction code	D/E
14.4. Packing group	
14.5. Environmental hazards	No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user RID UN1993 14.1. UN number FLAMMABLE LIQUID, N.O.S. (vapour pressure at 50 °C more than 110 kPa) (Ethanol, 14.2. UN proper shipping (2,2-Dimethyl-1,3-dioxolan-4-yl)methanol) name 14.3. Transport hazard class(es) Class 3 Subsidiary risk -3 Label(s) Ш 14.4. Packing group 14.5. Environmental hazards No. 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user ADN UN1993 14.1. UN number FLAMMABLE LIQUID, N.O.S. (Ethanol, (2,2-Dimethyl-1,3-dioxolan-4-yl)methanol) 14.2. UN proper shipping name 14.3. Transport hazard class(es) Class 3 Subsidiary risk -3 Label(s) 14.4. Packing group Ш 14.5. Environmental hazards No. Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions for user IATA 14.1. UN number UN1993 14.2. UN proper shipping Flammable liquid, n.o.s. (Ethanol, (2,2-Dimethyl-1,3-dioxolan-4-yl)methanol) name 14.3. Transport hazard class(es) 3 Class Subsidiary risk \_ 14.4. Packing group Ш 14.5. Environmental hazards Yes 3H ERG Code Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions for user Other information Allowed with restrictions. Passenger and cargo aircraft Allowed with restrictions. Cargo aircraft only IMDG 14.1. UN number UN1993 14.2. UN proper shipping FLAMMABLE LIQUID, N.O.S. (Ethanol, (2,2-Dimethyl-1,3-dioxolan-4-yl)methanol), MARINE POLLUTANT name 14.3. Transport hazard class(es) Class 3 Subsidiary risk \_ Ш 14.4. Packing group 14.5. Environmental hazards Yes Marine pollutant EmS F-E, S-E Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions for user 14.7. Maritime transport in bulk Not established. according to IMO instruments

### ADN; ADR; IATA; IMDG; RID



Marine pollutant



IMDG Regulated Marine Pollutant.

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### EU regulations

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.
- Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.
- Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.
- Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Austria: 2NHG-TAPW-AY2Q-0KRA Belgium: 2NHG-TAPW-AY2Q-0KRA Bulgaria: 2NHG-TAPW-AY2Q-0KRA Croatia: 2NHG-TAPW-AY2Q-0KRA Cyprus: 2NHG-TAPW-AY2Q-0KRA Czech Republic: 2NHG-TAPW-AY2Q-0KRA Denmark: 2NHG-TAPW-AY2Q-0KRA Estonia: 2NHG-TAPW-AY2Q-0KRA EU: 2NHG-TAPW-AY2Q-0KRA Finland: 2NHG-TAPW-AY2Q-0KRA France: 2NHG-TAPW-AY2Q-0KRA Germany: 2NHG-TAPW-AY2Q-0KRA Great Britain: 2NHG-TAPW-AY2Q-0KRA Greece: 2NHG-TAPW-AY2Q-0KRA Hungary: 2NHG-TAPW-AY2Q-0KRA Iceland: 2NHG-TAPW-AY2Q-0KRA Ireland: 2NHG-TAPW-AY2Q-0KRA Italy: 2NHG-TAPW-AY2Q-0KRA Latvia: 2NHG-TAPW-AY2Q-0KRA Lithuania: 2NHG-TAPW-AY2Q-0KRA Luxembourg: 2NHG-TAPW-AY2Q-0KRA Malta: 2NHG-TAPW-AY2Q-0KRA Netherlands: 2NHG-TAPW-AY2Q-0KRA Norway: 2NHG-TAPW-AY2Q-0KRA Poland: 2NHG-TAPW-AY2Q-0KRA Portugal: 2NHG-TAPW-AY2Q-0KRA Romania: 2NHG-TAPW-AY2Q-0KRA Slovakia: 2NHG-TAPW-AY2Q-0KRA Slovenia: 2NHG-TAPW-AY2Q-0KRA Spain: 2NHG-TAPW-AY2Q-0KRA Sweden: 2NHG-TAPW-AY2Q-0KRA

### Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

### **Restrictions on use**

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Ethanol (CAS 64-17-5)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

### Other EU regulations

### Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

benzyl benzoate (CAS 120-51-4) Ethanol (CAS 64-17-5)

Other regulations	The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.
National regulations	Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.
15.2. Chemical safety assessment	No Chemical Safety Assessment has been carried out.

### **SECTION 16: Other information**

#### List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).
CAS: Chemical Abstract Service.
CEN: European Committee for Standardization.
IATA: International Air Transport Association.
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
IMDG: International Maritime Dangerous Goods.
MAC: Maximum Allowed Concentration.
MARPOL: International Convention for the Prevention of Pollution from Ships.
PBT: Persistent, bioaccumulative and toxic.
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.
STEL: Short term exposure limit.

	TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value. vPvB: Very persistent and very bioaccumulative.
References	Not available.
Information on evaluation method leading to the classification of mixture	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
Full text of any statements, which are not written out in full	
under sections 2 to 15	<ul> <li>H225 Highly flammable liquid and vapour.</li> <li>H226 Flammable liquid and vapour.</li> <li>H302 Harmful if swallowed.</li> <li>H304 May be fatal if swallowed and enters airways.</li> <li>H315 Causes skin irritation.</li> <li>H317 May cause an allergic skin reaction.</li> <li>H319 Causes serious eye irritation.</li> <li>H400 Very toxic to aquatic life.</li> <li>H410 Very toxic to aquatic life with long lasting effects.</li> <li>H411 Toxic to aquatic life with long lasting effects.</li> </ul>
<b>Revision information</b>	None.
Training information	Follow training instructions when handling this material.
Disclaimer	Yankee Candle s.r.o. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.