

SAFETY DATA SHEET

Version #: 05 Issue date: 20-January-2023 Revision date: 28-May-2023 Supersedes date: 06-May-2023

	of the substance/mixture and of the company/undertaking
1.1. Product identifier Trade name or designation of the mixture	Yankee Candle Wild Orchid Reed Diffuser Refill - 1745738E
Registration number	_
Synonyms	None.
Product code	1745738E
1.2. Relevant identified uses of t Identified uses	the substance or mixture and uses advised against Air Care Products
Uses advised against	None known.
1.3. Details of the supplier of the	e safety data sheet
Company name	Yankee Candle Company (Europe) Limited
Company Address	Poplar Way East, Cabot Park
	Avonmouth
	Bristol
	United Kingdom
	BS11 0YH
1.4. Emergency telephone numb	ber
General in EU	112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Austria National Poisons Information Centre	+431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Belgium National Poisons Control Centre	070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Bulgaria National Toxicological Information Centre	+359 2 9154233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Czech Republic National Poisons Information Centre	+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Denmark National Poisons Control Centre	+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Estonia National Poisons Information Centre	16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)
Finland National Poison Information Centre	(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
France National Poisons Control Centre	ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Hungary National Emergency Phone Number	36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Lithuania Neatidėliotina informacija apsinuodijus	+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Malta Accident and Emergency Department	2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Netherlands National Poisons Information Centre (NVIC)	030-274 88 88 (Only for the purpose of informing medical personnel in cases of acute intoxications)

1.4. Emergency telephone number

Norway Norwegian Poison Information Centre	22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Portugal Poison Centre	800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Romania Biroul RSI si Informare Toxicologica	021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be available for the Emergency Service.)
Slovakia National Toxicological Information Centre	+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Sweden National Poison Information Centre	112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Switzerland Tox Info Suisse	145 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards		
Flammable liquids	Category 2	H225 - Highly flammable liquid and vapour.
Health hazards		
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Skin sensitisation	Category 1B	H317 - May cause an allergic skin reaction.
Environmental hazards		
Hazardous to the aquatic environment, long-term aquatic hazard	Category 3	H412 - Harmful to aquatic life with long lasting effects.
2.2. Label elements		
Label according to Regulation (EC) No. 1272/20	08 as amended	
UFI:		
Austria: 4CSX-	WS78-9Q7H-NKVN	

Austria: 4CSX-WS78-9Q7H-NKVN	
Belgium: 4CSX-WS78-9Q7H-NKVN	
Bulgaria: 4CSX-WS78-9Q7H-NKVN	
Croatia: 4CSX-WS78-9Q7H-NKVN	
Cyprus: 4CSX-WS78-9Q7H-NKVN	
Czech Republic: 4CSX-WS78-9Q7H-	NKVN
Denmark: 4CSX-WS78-9Q7H-NKVN	
Estonia: 4CSX-WS78-9Q7H-NKVN	
EU: 4CSX-WS78-9Q7H-NKVN	
Finland: 4CSX-WS78-9Q7H-NKVN	
France: 4CSX-WS78-9Q7H-NKVN	
Germany: 4CSX-WS78-9Q7H-NKVN	
Great Britain: 4CSX-WS78-9Q7H-NK	VN
Greece: 4CSX-WS78-9Q7H-NKVN	
Hungary: 4CSX-WS78-9Q7H-NKVN	
Iceland: 4CSX-WS78-9Q7H-NKVN	
Ireland: 4CSX-WS78-9Q7H-NKVN	
Italy: 4CSX-WS78-9Q7H-NKVN	
Latvia: 4CSX-WS78-9Q7H-NKVN	
Lithuania: 4CSX-WS78-9Q7H-NKVN	
Luxembourg: 4CSX-WS78-9Q7H-NK	√N
Malta: 4CSX-WS78-9Q7H-NKVN	
Netherlands: 4CSX-WS78-9Q7H-NK\	/N
Norway: 4CSX-WS78-9Q7H-NKVN	
Poland: 4CSX-WS78-9Q7H-NKVN	
Portugal: 4CSX-WS78-9Q7H-NKVN	
Romania: 4CSX-WS78-9Q7H-NKVN	
Slovakia: 4CSX-WS78-9Q7H-NKVN	
Slovenia: 4CSX-WS78-9Q7H-NKVN	
Spain: 4CSX-WS78-9Q7H-NKVN	
Sweden: 4CSX-WS78-9Q7H-NKVN	
Benzoic acid 2-hydroxy- hexyl ester	Renzvl

Contains:

Benzoic acid, 2-hydroxy-, hexyl ester, Benzyl salicylate, Cyclamen aldehyde, Hexyl Cinnamal, Hydroxycitronellal, Isocyclemone E, Linalool, Oils, orange, sweet

Hazard pictograms



Signal word	Danger
Hazard statements	
H225	Highly flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.
Precautionary statements	
Prevention	
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P235	Keep cool.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing mist/vapours.
P264	Wash thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
Response	
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use appropriate media to extinguish.
Storage	
P403 + P235	Not applicable. Store in a well-ventilated place. Keep cool.
Disposal	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Supplemental label information	None.
2.3. Other hazards	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Ethanol	70 - 80) 64-17-5 200-578-6	-	603-002-00-5	
	Classification: Flam. Lie	q. 2;H225, Eye Irrit. 2;⊦	1319		
Hexyl Cinnamal	1 - 3	101-86-0 202-983-3	-	-	
	Classification: Skin Ser Chronic		cute 1;H400(M=1), Aquatic		
Benzyl salicylate	≤ 1	118-58-1 204-262-9	-	607-754-00-5	
	Classification: Eye Irrit.	2;H319, Skin Sens. 18	3;H317, Aquatic Chronic 3;H	412	

Chemical name	%	CAS-No. / EC No.	REACH Registration No	. Index No. Notes
Galaxolide	≤ 0,3	1222-05-5 214-946-9	-	603-212-00-7
Class	ification: Aquatic A	cute 1;H400, Aquatic	Chronic 1;H410	
Hydroxycitronellal	≤ 0,3	107-75-5 203-518-7	-	-
Class	ification: Eye Irrit. 2	;H319, Skin Sens. 1E	3;H317	
Linalool	≤ 0,3	78-70-6 201-134-4	-	603-235-00-2
		-	319, Skin Sens. 1B;H317	
Benzoic acid, 2-hydroxy-, he	•	6259-76-3 228-408-6	-	-
	Chronic 1	H410(M=1)	cute 1;H400(M=1), Aquatic	
Cyclamen aldehyde	≤ 0,2	103-95-7 203-161-7	-	-
	ification: Skin Irrit.	2;H315, Skin Sens. 1	B;H317, Aquatic Chronic 3;	H412
Isocyclemone E	≤ 0,2	54464-57-2 259-174-3	-	-
Class			B;H317, Aquatic Chronic 2;	;H411
Oils, orange, sweet	≤ 0,2	8008-57-9 616-926-9	-	-
Class		2;H225, Skin Irrit. 2;l sp. Tox. 1;H304, Aqu	H315, Eye Irrit. 2;H319, Ski atic Chronic 2;H411	n Sens.
Lyral	≤ 0,1	31906-04-4 250-863-4	-	605-040-00-8
Class	ification: Skin Sens	. 1A;H317		
ATE: Acute toxicity estimate M: M-factor vPvB: very persistent and ve PBT: persistent, bioaccumul #: This substance has been All concentrations are in per	ery bioaccumulative s ative and toxic subst assigned Union worl	ance. <place exposure="" limit<="" th=""><th></th><th>percent by volume.</th></place>		percent by volume.
Composition comments	The full text for a	II H-statements is dis	played in section 16.	
SECTION 4: First aid mea	asures			
General information				cal personnel are aware of the Wash contaminated clothing
4.1. Description of first aid mea	asures			
Inhalation			mptoms develop or persist	
Skin contact	eczema or other	skin disorders: Seek	liately and wash skin with s medical attention and take	along these instructions.
Eye contact	present and easy	to do. Continue rinsi	ng. Get medical attention if	s. Remove contact lenses, if irritation develops and persists.
Ingestion		t medical attention if	•	, tearing, redness, swelling, and
4.2. Most important symptoms and effects, both acute and delayed			n allergic skin reaction. De	
4.3. Indication of any immediate medical attention and special treatment needed	immediately. Whi	le flushing, remove c inue flushing during t	and treat symptomatically. lothes which do not adhere ransport to hospital. Keep v	
SECTION 5: Firefighting	measures			
General fire hazards	Highly flammable	liquid and vapour.		
5.1. Extinguishing media Suitable extinguishing media	Water fog. Alcoho	bl resistant foam. Dry	chemical powder. Carbon	dioxide (CO2).
	Onchild Devel Difference			

Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special fire fighting procedures	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
SECTION 6: Accidental rel	ease measures
6.1. Personal precautions, prote	ctive equipment and emergency procedures
For non-emergency personnel	Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
For emergency responders	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Ventilate closed spaces before entering them. Avoid breathing mist/vapours. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.
6.2. Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent entry into waterways, sewer, basements or confined areas.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use.
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.
SECTION 7: Handling and	storage
7.1. Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBI. II, no. 184/2001

Components	Туре	Value	
Ethanol (CAS 64-17-5)	Ceiling	3800 mg/m3	
		2000 ppm	
	MAK	1900 mg/m3	
		1000 ppm	

Observe industrial sector guidance on best practices.

Components	/alues Type	Value
Ethanol (CAS 64-17-5)	TWA	1907 mg/m3
		1000 ppm
Bulgaria. OELs. Regulatior Components	ו No 13 on protection of workers aga Type	inst risks of exposure to chemical agents at work Value
Ethanol (CAS 64-17-5)	TWA	1000 mg/m3
Croatia. Dangerous Substa	ance Exposure Limit Values in the We	orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/0
Components	Туре	Value
Ethanol (CAS 64-17-5)	MAC	1900 mg/m3
		1000 ppm
Czech Republic. OELs. Go	vernment Decree 361	
Components	Туре	Value
Ethanol (CAS 64-17-5)	Ceiling	3000 mg/m3
	TWA	1000 mg/m3
Denmark. Exposure Limit		
Components	Туре	Value
Ethanol (CAS 64-17-5)	TLV	1900 mg/m3
		1000 ppm
Estonia. OELs. Occupation Components	nal Exposure Limits of Hazardous Su Type	bstances (Regulation No. 105/2001, Annex), as amended Value
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3
		1000 ppm
	TWA	1000 mg/m3
		500 ppm
Finland. Workplace Exposi	ure Limits	
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	2500 mg/m3
		1300 ppm
	TWA	1900 mg/m3
		1000 ppm
	alues (VLEP) for Occupational Expos Type	ure to Chemicals in France, INRS ED 984 Value
Components		ure to Chemicals in France, INRS ED 984
Components Ethanol (CAS 64-17-5)	Туре	ure to Chemicals in France, INRS ED 984 Value
Components Ethanol (CAS 64-17-5) Regulatory status: Ir	Type VLE ndicative limit (VL)	ure to Chemicals in France, INRS ED 984 Value
Components Ethanol (CAS 64-17-5) Regulatory status: Ir	Type VLE ndicative limit (VL) ndicative limit (VL)	ure to Chemicals in France, INRS ED 984 Value 9500 mg/m3 5000 ppm
Components Ethanol (CAS 64-17-5) Regulatory status: Ir Regulatory status: Ir	Type VLE ndicative limit (VL) ndicative limit (VL) VME	ure to Chemicals in France, INRS ED 984 Value 9500 mg/m3
Components Ethanol (CAS 64-17-5) Regulatory status: Ir Regulatory status: Ir	Type VLE ndicative limit (VL) ndicative limit (VL)	ure to Chemicals in France, INRS ED 984 Value 9500 mg/m3 5000 ppm 1900 mg/m3
Components Ethanol (CAS 64-17-5) Regulatory status: Ir Regulatory status: Ir Regulatory status: Ir	Type VLE ndicative limit (VL) ndicative limit (VL) VME ndicative limit (VL)	ure to Chemicals in France, INRS ED 984 Value 9500 mg/m3 5000 ppm
Components Ethanol (CAS 64-17-5) Regulatory status: Ir Regulatory status: Ir Regulatory status: Ir Regulatory status: Ir	Type VLE Indicative limit (VL) VME Indicative limit (VL) Indicative limit (VL)	ure to Chemicals in France, INRS ED 984 Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm
Components Ethanol (CAS 64-17-5) Regulatory status: Ir Regulatory status: Ir Regulatory status: Ir Regulatory status: Ir Germany. DFG MAK List (a in the Work Area (DFG)	Type VLE ndicative limit (VL) VME ndicative limit (VL) ndicative limit (VL) ndicative limit (VL)	ure to Chemicals in France, INRS ED 984 Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm
Components Ethanol (CAS 64-17-5) Regulatory status: Ir Regulatory status: Ir Regulatory status: Ir Regulatory status: Ir Germany. DFG MAK List (a in the Work Area (DFG) Components	Type VLE ndicative limit (VL) VME ndicative limit (VL) ndicative limit (VL) ndicative limit (VL) ndicative limit (VL) Idvisory OELs). Commission for the I	ure to Chemicals in France, INRS ED 984 Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm Investigation of Health Hazards of Chemical Compounds Value
Components Ethanol (CAS 64-17-5) Regulatory status: Ir Regulatory status: Ir Regulatory status: Ir Regulatory status: Ir Germany. DFG MAK List (a in the Work Area (DFG)	Type VLE ndicative limit (VL) VME ndicative limit (VL) ndicative limit (VL) ndicative limit (VL)	ure to Chemicals in France, INRS ED 984 Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm Investigation of Health Hazards of Chemical Compounds Value 380 mg/m3
Components Ethanol (CAS 64-17-5) Regulatory status: Ir Regulatory status: Ir Regulatory status: Ir Regulatory status: Ir Germany. DFG MAK List (a in the Work Area (DFG) Components	Type VLE ndicative limit (VL) VME ndicative limit (VL) ndicative limit (VL) ndicative limit (VL) ndicative limit (VL) Idvisory OELs). Commission for the I	ure to Chemicals in France, INRS ED 984 Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm Investigation of Health Hazards of Chemical Compounds Value
Components Ethanol (CAS 64-17-5) Regulatory status: Ir Regulatory status: Ir Regulatory status: Ir Regulatory status: Ir Germany. DFG MAK List (a in the Work Area (DFG) Components Ethanol (CAS 64-17-5)	Type VLE ndicative limit (VL) VME ndicative limit (VL) ndicative limit (VL) ndicative limit (VL) ndicative limit (VL) Idvisory OELs). Commission for the I	ure to Chemicals in France, INRS ED 984 Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm Investigation of Health Hazards of Chemical Compounds Value 380 mg/m3 200 ppm
Components Ethanol (CAS 64-17-5) Regulatory status: Ir Regulatory status: Ir Regulatory status: Ir Regulatory status: Ir Germany. DFG MAK List (a in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Germany. TRGS 900, Limit	Type VLE ndicative limit (VL) VME ndicative limit (VL) ndvisory OELs). Commission for the I Type TWA Values in the Ambient Air at the Wor	ure to Chemicals in France, INRS ED 984 Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm Investigation of Health Hazards of Chemical Compounds Value 380 mg/m3 200 ppm

Ethanol (CAS 64-17-5) TWA 1900 mg/m3 1000 ppm Hungary, OELs. Joint Decree on Chemical Safety of Workplaces Components Type Value Ethanol (CAS 64-17-5) STEL 3800 mg/m3 TWA 1900 mg/m3 teeland. OELs. Regulation 154/1999 on occupational exposure limits Components Type Value Ethanol (CAS 64-17-5) TWA 1900 mg/m3 troland. Occupational Exposure Limits Components Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm troland. Occupational Exposure Limits Components Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm tate). Occupational Exposure Limits Components Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm Latvia. OELs. Cocupational exposure limit values of chemical substances in work environment Components Type Value Ethanol (CAS 64-17-5) STEL 1000 mg/m3 Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Norway, Administrative Norms for Contaminants in the Workplace Components Type Value Ethanol (CAS 64-17-5) TLV 9500 mg/m3 Norway, Administrative Norms for Contaminants in the Workplace Components Type Value Ethanol (CAS 64-17-5) TLV 950 mg/m3 Norway, Administrative Norms for Contaminants in the Workplace Components Type Value Ethanol (CAS 64-17-5) TLV 950 mg/m3 Norway, Administrative Norms for Contaminants in the Workplace Components Type Value Ethanol (CAS 64-17-5) TLV 950 mg/m3 Portugal, VLEs. Norm on occupational exposure to chemical agents (NP 1756) Components Type Value Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Boo mg/m3 Portugal, VLEs. Norm on occupational exposure to chemical agents (NP 1756) Components Type Value Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Boo mg/m3 Portugal, VLEs. Norm on occupational exposure to chemical agents the workplace Components Type Value Ethanol (CAS 64-17-5) TWA 1000 ppm Romania. OELs. Protection of wor	Greece. OELs (Decree No. 90/199 Components	99, as amended) Type	Value
Hungary. CELs. Joint Decree on Chemical Safety of Workplaces ComponentsValueEthanol (CAS 64-17-5)STEL TVVA3800 mg/m3 1900 mg/m3Leadan. OELs. Regulation 154/1999 on occupational exposure limits ComponentsYalueEthanol (CAS 64-17-5)TVVA1900 mg/m3 1000 ppmIreland. Occupational Exposure Limits ComponentsTypeValueEthanol (CAS 64-17-5)STEL1000 ppmIreland. Occupational Exposure Limits ComponentsTypeValueEthanol (CAS 64-17-5)STEL1000 ppmItaly. Occupational Exposure Limits ComponentsTypeValueEthanol (CAS 64-17-5)STEL1000 ppmEthanol (CAS 64-17-5)STEL1000 ppmEthanol (CAS 64-17-5)STEL1000 mg/m3Ethanol (CAS 64-17-5)TV/A1000 mg/m3Ethanol (CAS 64-17-5)STEL1900 mg/m3Ethanol (CAS 64-17-5)STEL1900 mg/m3ComponentsTypeValueEthanol (CAS 64-17-5)STEL1900 mg/m3ComponentsTypeValueEthanol (CAS 64-17-5)STEL1900 mg/m3ComponentsTypeValueEthanol (CAS 64-17-5)TLV800 mg/m3ComponentsTypeValueEthanol (CAS 64-17-5)TLV800 mg/m3ComponentsTypeValueEthanol (CAS 64-17-5)TLV800 mg/m3Door promontsTypeValueEthanol (CAS 64-17-5)TLV800 mg/m3Door pro	Ethanol (CAS 64-17-5)	TWA	1900 mg/m3
ComponentsTypeValueEthanol (CAS 64-17-5)STEL3800 mg/m3Iceland. OELs. Regulation 154/1999 on occupational exposure limits1900 mg/m3ComponentsTypeValueEthanol (CAS 64-17-5)TWA1900 mg/m3Ireland. Occupational Exposure Limits1000 ppmComponentsTypeValueEthanol (CAS 64-17-5)STEL1000 ppmItaly. Occupational Exposure Limits1000 ppmComponentsTypeValueEthanol (CAS 64-17-5)STEL1000 ppmItaly. Occupational Exposure Limits1000 ppmComponentsTypeValueEthanol (CAS 64-17-5)STEL1000 ppmItaly. OCcupational exposure limit values of chemical substances in work environmentComponentsTypeValueEthanol (CAS 64-17-5)TWA1000 mg/m3Ithuania. OELs. Limit Values for Chemical Substances, General RequirementsComponentsComponentsTypeValueEthanol (CAS 64-17-5)STEL1900 mg/m3More and	, , , , , , , , , , , , , , , , , , ,		
ComponentsTypeValueEthanol (CAS 64-17-5)STEL3800 mg/m3Iceland. OELs. Regulation 154/1999 on occupational exposure limits1900 mg/m3ComponentsTypeValueEthanol (CAS 64-17-5)TWA1900 mg/m3Ireland. Occupational Exposure Limits1000 ppmComponentsTypeValueEthanol (CAS 64-17-5)STEL1000 ppmItaly. Occupational Exposure Limits1000 ppmComponentsTypeValueEthanol (CAS 64-17-5)STEL1000 ppmItaly. Occupational Exposure Limits1000 ppmComponentsTypeValueEthanol (CAS 64-17-5)STEL1000 ppmItaly. OCcupational exposure limit values of chemical substances in work environmentComponentsTypeValueEthanol (CAS 64-17-5)TWA1000 mg/m3Ithuania. OELs. Limit Values for Chemical Substances, General RequirementsComponentsComponentsTypeValueEthanol (CAS 64-17-5)STEL1900 mg/m3More and	Hungary, OELs, Joint Decree on	Chemical Safety of Workplace	s
TWA 1900 mg/m3 Ioeland, OELS. Regulation 154/1999 on occupational exposure limits Value Ethanol (CAS 64-17-5) TWA 1900 mg/m3 1000 ppm Ireland, Occupational Exposure Limits Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm taly, Occupational Exposure Limits Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm taly, Occupational Exposure Limits Type Value Components Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm Latvia, OELs, Occupational exposure limit values of chemical substances in work environment Components Components Type Value Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Stop ppm TWA 1000 ppm TWA 1000 mg/m3 500 ppm Netwerlands, OELs (binding) Components Type Components Type Value Ethanol (CAS 64-17-5)			
Iceland. OELs. Regulation 154/1999 on occupational exposure limits Ype Value Ethanol (CAS 64-17-5) TWA 1900 mg/m3 1000 ppm Ireland. Occupational Exposure Limits Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm Italy, Occupational Exposure Limits Type Value Components Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm Latvia, Occupational Exposure Limits Type Value Components Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm Latvia, Occupational exposure limit values of chemical substances in work environment Components Components Type Value Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Littuania. OELs. Limit Values for Chemical Substances, General Requirements 000 ppm Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 TWA 1000 pg/m3 500 ppm Netherlands. OELs (binding) Type Value Components	Ethanol (CAS 64-17-5)	STEL	3800 mg/m3
Components Type Value Ethanol (CAS 64-17-5) TWA 1900 mg/m3 1000 ppm Ireland. Occupational Exposure Limits Yppe Value Components Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm taly. Occupational Exposure Limits Components Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm Latvia. OELs. Occupational exposure limit values of chemical substances in work environment Components Components Type Value Value Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Ithuania. OELs. Limit Values for Chemical Substances, General Requirements Components Type Value Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Ethanol (CAS 64-17-5) STEL 1900 mg/m3 500 ppm 500 ppm Netherlands. OELs (binding) TWA 260 mg/m3 500 ppm Components Type Value Value Ethanol (CAS 64-17-5) TUV 960 mg/m3 Components Type Value Value		TWA	1900 mg/m3
Ethanol (CAS 64-17-5) TWA 1900 mg/m3 1000 ppm Ireland. Occupational Exposure Limits Components Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm Haly, Occupational Exposure Limits Components Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm Latvia, OELs. Cocupational exposure limit values of chemical substances in work environment Components Type Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 TWA 1000 ppm TWA 1000 ppm Netherlands. OELs (binding) Type Value Components Type Value Ethanol (CAS 64-17-5) TLV 260 mg/m3 TWA 260 mg/m3 500 ppm Norway. Administrative Norms for Contaminants in the Workplace Components Components Type Value Ethanol (CAS 64-17-5) TLV 950 mg/m3 <td>Iceland. OELs. Regulation 154/19</td> <td>99 on occupational exposure</td> <td>limits</td>	Iceland. OELs. Regulation 154/19	99 on occupational exposure	limits
Interland. Occupational Exposure Limits Components Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm Italy. Occupational Exposure Limits 0000 ppm Components Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm Latvia. OELs. Cocupational exposure limit values of chemical substances in work environment Components Components Type Value Ethanol (CAS 64-17-5) TWA 1000 ng/m3 Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components Components Type Value Ethanol (CAS 64-17-5) STEL 1900 ng/m3 Ethanol (CAS 64-17-5) STEL 1900 ng/m3 Ethanol (CAS 64-17-5) STEL 1900 ng/m3 Mode ppm TWA 1000 ppm Netherlands. OELs (binding) TWA 1000 ng/m3 Components Type Value Ethanol (CAS 64-17-5) STEL 1900 ng/m3 Norway. Administrative Norms for Contaminants in the Workplace Components Components Type Value Ethanol (CAS 64-17-5) TLV 950 ng/m3 Stot ppm Potenda itensities of harmful health factors in the work onviconment	Components	Туре	Value
Ireland. Occupational Exposure Limits Components Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm Italy. Occupational Exposure Limits Components Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm Latvia. OELs. Occupational exposure limit values of chemical substances in work environment Components Type Value Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Littuia. OELs. Limit Values for Chemical Substances, General Requirements Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 TWA 260 mg/m3 500 ppm Norway, Administrative Norms for Contaminants in the Workplace Components Type Value Ethanol (CAS 64-17-5) TLV 950 mg/m3 500 ppm Portugat. VLEs. Norm on occupational exposure to chemical agents (NP 1796)	Ethanol (CAS 64-17-5)	TWA	1900 mg/m3
ComponentsTypeValueEthanol (CAS 64-17-5)STEL1000 ppmttaly. Occupational Exposure LimitsTypeValueEthanol (CAS 64-17-5)STEL1000 ppmLatvia. OELs. Occupational exposure limit values of chemical substances in work environmentComponentsComponentsTypeValueEthanol (CAS 64-17-5)TWA1000 mg/m3Lithuania. OELs. Limit Values for Chemical Substances, General RequirementsComponentsComponentsTypeValueEthanol (CAS 64-17-5)STEL1900 mg/m31000 ppmTWA1000 ppmTWA1000 ppmTWA1000 ppmTWA260 mg/m3500 ppmTWA260 mg/m3ComponentsTypeValueEthanol (CAS 64-17-5)STEL1900 mg/m3TWA260 mg/m3TWA260 mg/m3Norway, Administrative Norms for Contaminants in the WorkplaceS00 ppmComponentsTypeValueEthanol (CAS 64-17-5)TLV950 mg/m3Norway, Administrative Norms for Contaminants in the WorkplaceS00 ppmPoland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of narmful health factors in the work environment, Journal of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of narmful health factors in the work environment, Journal of L			1000 ppm
Ethanol (CAS 64-17-5) STEL 1000 ppm Italy. Occupational Exposure Limits Components Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm Latvia. OELs. Cocupational exposure limit values of chemical substances in work environment Components Type Value Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components 1000 ppm Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Netherlands. OELs (binding) Type Value Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Norway. Administrative Norms for Contaminants in the Workplace Components Components Type Value Ethanol (CAS 64-17-5) TLV 950 mg/m3 Norway. Administrative Norms for Contaminants in the Workplace S00 ppm Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Components Type Value Value Ethanol (CAS 64-17-5) TWA 1900 mg/m3 Portugal.		_imits	
Italy, Occupational Exposure Limits Type Value Ethanol (CAS 64-17-5) STEL 1000 ppm Latvia, OELs, Occupational exposure limit values of chemical substances in work environment Components Type Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Litthuania, OELs, Limit Values for Chemical Substances, General Requirements Components Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Stop oppm TWA 1000 mg/m3 Mathematical Substances STEL 1900 mg/m3 Stop oppm TWA 260 mg/m3 Netherlands, OELs (binding) Type Value Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 TWA 260 mg/m3 500 ppm Norway, Administrative Norms for Contaminants in the Workplace Components 500 ppm Components Type Value Value 1000 pg/m3 Poland, Ordinance of the Minister of Labour and Social Policy on 6	Components	Туре	Value
ComponentsTypeValueEthanol (CAS 64-17-5)STEL1000 ppmLatvia, OELs. Occupational exposure limit values of chemical substances in work environment Components1000 mg/m3Ethanol (CAS 64-17-5)TWA1000 mg/m3Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components1000 mg/m3Lithuania. OELs. Limit Values for Chemical Substances, General Requirements TypeValueEthanol (CAS 64-17-5)STEL1900 mg/m3Ethanol (CAS 64-17-5)STEL1000 mg/m3TWA1000 mg/m3500 ppmNetherlands. OELs (binding) ComponentsTypeValueComponentsTypeValueEthanol (CAS 64-17-5)STEL1900 mg/m3Norway. Administrative Norms for Contaminants in the Workplace ComponentsTypeValueEthanol (CAS 64-17-5)TLV950 mg/m3Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817ComponentsTypeValueEthanol (CAS 64-17-5)TWA1900 mg/m3Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) ComponentsTypeComponentsTypeValueEthanol (CAS 64-17-5)TWA1900 mg/m3Ethanol (CAS 64-17-5)TWA1900 mg/m3Ethanol (CAS 64-17-5)TWA1900 mg/m3Ethanol (CAS 64-17-5)TWA1900 mg/m3Ethanol (CAS 64-17-5)	Ethanol (CAS 64-17-5)	STEL	1000 ppm
Ethanol (CAS 64-17-5) STEL 1000 ppm Latvia. OELs. Occupational exposure limit values of chemical substances in work environment Value Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components Value Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm Netherlands. OELs (binding) TVPe Value Value Components Type Value Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 500 ppm Netherlands. OELs (binding) TVPe Value Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 500 ppm Norway. Administrative Norms for Contaminants in the Workplace Components Type Value Ethanol (CAS 64-17-5) TLV 950 mg/m3 500 ppm Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible components Type Value TVP Value		iits	
Latvia. OELs. Occupational exposure limit values of chemical substances in work environment Components Type Value Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components Type Value Ethanol (CAS 64-17-5) STEL 19900 mg/m3 TWA 1000 ng/m3 500 ppm Netherlands. OELs (binding) Components Type Value Ethanol (CAS 64-17-5) STEL 19900 mg/m3 TWA 260 mg/m3 TWA 260 mg/m3 TWA 260 mg/m3 Norway. Administrative Norms for Contaminants in the Workplace Components Type Value Ethanol (CAS 64-17-5) TLV 950 mg/m3 500 ppm Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 Components Type Value Ethanol (CAS 64-17-5) TWA 1900 mg/m3 Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Components Type Value Ethanol (CAS 64-17-5) TWA 1900 mg/m3 Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Components Type Value Ethanol (CAS 64-17-5) TWA 1000 ppm Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Components Type Value Ethanol (CAS 64-17-5) TWA 1000 ppm Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Components Type Value	Components	Туре	Value
ComponentsTypeValueEthanol (CAS 64-17-5)TWA1000 mg/m3Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components1900 mg/m3Ethanol (CAS 64-17-5)STEL1900 mg/m3Ethanol (CAS 64-17-5)STEL1000 ppmTWA1000 mg/m3500 ppm1000 mg/m3Store500 ppmNetherlands. OELs (binding)TVPValueComponentsTypeValueEthanol (CAS 64-17-5)STEL1900 mg/m3TWA260 mg/m3TWANorway. Administrative Norms for Contaminants in the Workplace ComponentsTypeComponentsTypeValueEthanol (CAS 64-17-5)TLV950 mg/m3 500 ppmPoland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 ComponentsTypePortugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) ComponentsTypeValueEthanol (CAS 64-17-5)TWA1900 mg/m3Portugal. VLEs. Norm on occupational exposure to chemical agents at the workplace ComponentsTypeComponentsTypeValueEthanol (CAS 64-17-5)TWA1000 ppmRomania. OELs. Protection of workers from exposure to chemical agents at the workplace ComponentsTypeComponentsTypeValueEthanol (CAS 64-17-5)TWA1000 ppmRomania. OELs. Protection of workers from exposu	Ethanol (CAS 64-17-5)	STEL	1000 ppm
ComponentsTypeValueEthanol (CAS 64-17-5)TWA1000 mg/m3Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components1900 mg/m3Ethanol (CAS 64-17-5)STEL1900 mg/m3Ethanol (CAS 64-17-5)STEL1000 ppmTWA1000 mg/m3500 ppm1000 mg/m3Store500 ppmNetherlands. OELs (binding)TVPValueComponentsTypeValueEthanol (CAS 64-17-5)STEL1900 mg/m3TWA260 mg/m3TWANorway. Administrative Norms for Contaminants in the Workplace ComponentsTypeComponentsTypeValueEthanol (CAS 64-17-5)TLV950 mg/m3 500 ppmPoland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 ComponentsTypePortugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) ComponentsTypeValueEthanol (CAS 64-17-5)TWA1900 mg/m3Portugal. VLEs. Norm on occupational exposure to chemical agents at the workplace ComponentsTypeComponentsTypeValueEthanol (CAS 64-17-5)TWA1000 ppmRomania. OELs. Protection of workers from exposure to chemical agents at the workplace ComponentsTypeComponentsTypeValueEthanol (CAS 64-17-5)TWA1000 ppmRomania. OELs. Protection of workers from exposu	Latvia. OELs. Occupational expo	sure limit values of chemical s	substances in work environment
Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Netherlands. OELs (binding) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 TWA 260 mg/m3 Norway. Administrative Norms for Contaminants in the Workplace Components Type Value Ethanol (CAS 64-17-5) TLV 950 mg/m3 500 ppm Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 Components Type Value Ethanol (CAS 64-17-5) TWA 1900 mg/m3 Potugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Components Type Value Ethanol (CAS 64-17-5) TWA 1900 ppm Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Components Type Value Ethanol (CAS 64-17-5) STEL 5000 ppm Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Components Type Value Ethanol (CAS 64-17-5) TWA 1900 ppm Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Components Type Value Ethanol (CAS 64-17-5) TWA 1900 ppm			
ComponentsTypeValueEthanol (CAS 64-17-5)STEL1900 mg/m3 1000 ppmTWA1000 mg/m3 500 ppmNetherlands. OELs (binding) ComponentsTypeValueEthanol (CAS 64-17-5)STEL1900 mg/m3 TWAEthanol (CAS 64-17-5)STEL1900 mg/m3 TWANorway. Administrative Norms for Contaminants in the Workplace ComponentsTypeValueEthanol (CAS 64-17-5)TLV950 mg/m3 500 ppmPoland. Ocdinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 ComponentsTypePoland. (CAS 64-17-5)TWA1900 mg/m3Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) ComponentsTypePortugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) ComponentsTypePortugal. VLEs. Protection of workers from exposure to chemical agents at the workplace ComponentsTypeRomania. OELs. Protection of workers from exposure to chemical agents at the workplace ComponentsTypeComponentsTypeValueEthanol (CAS 64-17-5)STEL9500 mg/m3Ethanol (CAS 64-17-5)TWA1000 ppmEthanol (CAS 64-17-5)TWA1000 ppmEthanol (CAS 64-17-5)TWA1000 ppmRomania. OELs. Protection of workers from exposure to chemical agents at the workplace Components5000 ppmTWA1900 mg/m3	Ethanol (CAS 64-17-5)	TWA	1000 mg/m3
Ethanol (CAS 64-17-5) STEL 1900 mg/m3 TWA 1000 ppm TWA 1000 mg/m3 500 ppm Netherlands. OELs (binding) Components Type Ethanol (CAS 64-17-5) STEL TWA 1900 mg/m3 More and the state of	Lithuania. OELs. Limit Values fo	r Chemical Substances, Gener	ral Requirements
1000 ppm TWA 1000 mg/m3 500 ppm Netherlands. OELs (binding) Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 TWA 260 mg/m3 Norway. Administrative Norms for Contaminants in the Workplace Value Components Type Value Ethanol (CAS 64-17-5) TLV 950 mg/m3 Solo ppm Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 Components Type Value Ethanol (CAS 64-17-5) TWA 1900 mg/m3 Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Components Type Value Ethanol (CAS 64-17-5) TWA 1000 ppm Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Components Type Value Ethanol (CAS 64-17-5) STEL 9500 mg/m3 Dool ppm Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Components Type Value Et	Components	Туре	Value
TWA1000 mg/m3 500 ppmNetherlands. OELs (binding) ComponentsTypeValueEthanol (CAS 64-17-5)STEL1900 mg/m3 TWA260 mg/m3Norway. Administrative Norms for Contaminants in the Workplace ComponentsValueValueEthanol (CAS 64-17-5)TLV950 mg/m3 500 ppmPoland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 ComponentsYpeValueEthanol (CAS 64-17-5)TWA1900 mg/m3Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) ComponentsTypeValueEthanol (CAS 64-17-5)TWA1000 ppmRomania. OELs. Protection of workers from exposure to chemical agents at the workplace ComponentsTypeValueEthanol (CAS 64-17-5)TWA1000 ppmRomania. OELs. Protection of workers from exposure to chemical agents at the workplace ComponentsTypeValueEthanol (CAS 64-17-5)STEL9500 mg/m3 5000 ppmFundi (CAS 64-17-5)TWA1000 ppm	Ethanol (CAS 64-17-5)	STEL	1900 mg/m3
Sol ppmNetherlands. OELs (binding) ComponentsTypeValueEthanol (CAS 64-17-5)STEL1900 mg/m3TWA260 mg/m3Norway. Administrative Norms for Contaminants in the Workplace ComponentsValueEthanol (CAS 64-17-5)TLV950 mg/m3 500 ppmPoland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 ComponentsTypePoland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 ComponentsTypePortugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) ComponentsTypePortugal. VLEs. Norm on occupational exposure to chemical agents at the workplace ComponentsTypeEthanol (CAS 64-17-5)TWA1000 ppmRomania. OELs. Protection of workers from exposure to chemical agents at the workplace ComponentsSTELFuhanol (CAS 64-17-5)STEL9500 mg/m3 5000 ppmEthanol (CAS 64-17-5)STEL9500 mg/m3 5000 ppmTWA1900 mg/m35000 ppm			1000 ppm
Netherlands. OELs (binding) ComponentsTypeValueEthanol (CAS 64-17-5)STEL1900 mg/m3Norway. Administrative Norms for Contaminants in the Workplace ComponentsValueEthanol (CAS 64-17-5)TLV950 mg/m3Bethanol (CAS 64-17-5)TLV950 mg/m3Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817ComponentsTypeValueEthanol (CAS 64-17-5)TWA1900 mg/m3Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) ComponentsComponentsTypeValueEthanol (CAS 64-17-5)TWA1000 ppmRomania. OELs. Protection of workers from exposure to chemical agents at the workplace ComponentsComponentsTypeValueEthanol (CAS 64-17-5)STEL9500 mg/m3 5000 ppmTWA1000 ppm		TWA	1000 mg/m3
ComponentsTypeValueEthanol (CAS 64-17-5)STEL1900 mg/m3TWA260 mg/m3Norway. Administrative Norms for Contaminants in the Workplace260 mg/m3ComponentsTypeValueEthanol (CAS 64-17-5)TLV950 mg/m3Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817ComponentsTypeValueEthanol (CAS 64-17-5)TWA1900 mg/m3Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) ComponentsTypeValueEthanol (CAS 64-17-5)TWA1000 ppmRomania. OELs. Protection of workers from exposure to chemical agents at the workplace ComponentsTypeValueEthanol (CAS 64-17-5)STEL9500 mg/m3Formania. OELs. Protection of workers from exposure to chemical agents at the workplace ComponentsTypeValueEthanol (CAS 64-17-5)STEL9500 mg/m3Formania. OELs. Protection of workers from exposure to chemical agents at the workplace Components9500 mg/m3Formania. OELs. Protection of workers from exposure to chemical agents at the workplace Components9500 mg/m3Formania. OELs. Protection of workers from exposure to chemical agents at the workplace Components9500 mg/m3Formania. OELs. Protection of workers from exposure to chemical agents at the workplace Formania formania9500 mg/m3Formania. OELs. Protection of workers from exposure to chemical agents at the wo			500 ppm
Ethanol (CAS 64-17-5) STEL 1900 mg/m3 Norway. Administrative Norms for Contaminants in the Workplace Components Type Components Type Value Ethanol (CAS 64-17-5) TLV 950 mg/m3 Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 Components Type Value Ethanol (CAS 64-17-5) TWA 1900 mg/m3 Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Components Type Components Type Value Ethanol (CAS 64-17-5) TWA 1000 ppm Romania. OELs. Norm on occupational exposure to chemical agents at the workplace Components Type Value Value Ethanol (CAS 64-17-5) TWA 1000 ppm Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Components Type Value Value Ethanol (CAS 64-17-5) STEL 9500 mg/m3 Found (CAS 64-17-5) STEL 9500 mg/m3 Found (CAS 64-17-5) STEL	Netherlands. OELs (binding)		
TWA260 mg/m3Norway. Administrative Norms for Contaminants in the Workplace ComponentsValueEthanol (CAS 64-17-5)TLV950 mg/m3 500 ppmPoland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817ComponentsTypeValueEthanol (CAS 64-17-5)TWA1900 mg/m3Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) ComponentsValueEthanol (CAS 64-17-5)TWA1000 ppmRomania. OELs. Protection of workers from exposure to chemical agents at the workplace ComponentsYpeValueEthanol (CAS 64-17-5)STEL9500 mg/m3Ethanol (CAS 64-17-5)TWA1000 ppmRomania. OELs. Protection of workers from exposure to chemical agents at the workplace Components5000 ppmTypeValue1000 ppmEthanol (CAS 64-17-5)STEL9500 mg/m3Ethanol (CAS 64-17-5)TUA1900 mg/m3	Components	Туре	Value
Norway. Administrative Norms for Contaminants in the Workplace Components Type Value Ethanol (CAS 64-17-5) TLV 950 mg/m3 500 ppm Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 Components Type Value Ethanol (CAS 64-17-5) TWA 1900 mg/m3 Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Components Type Value Ethanol (CAS 64-17-5) TWA 1000 ppm Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Components Type Value Ethanol (CAS 64-17-5) STEL 9500 mg/m3 5000 ppm 5000 ppm Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Components Type Value Ethanol (CAS 64-17-5) STEL 9500 mg/m3 5000 ppm 5000 ppm Type Value Type Value Type	Ethanol (CAS 64-17-5)	STEL	1900 mg/m3
ComponentsTypeValueEthanol (CAS 64-17-5)TLV950 mg/m3 500 ppmPoland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 ComponentsTypeValueValueEthanol (CAS 64-17-5)TWA1900 mg/m3Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) ComponentsTypeValueEthanol (CAS 64-17-5)TWA1000 ppmRomania. OELs. Protection of workers from exposure to chemical agents at the workplace ComponentsTypeValueEthanol (CAS 64-17-5)STEL9500 mg/m3Fundol (CAS 64-17-5)TWA1900 mg/m3		TWA	260 mg/m3
Ethanol (CAS 64-17-5) TLV 950 mg/m3 500 ppm Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 Components Type Value Ethanol (CAS 64-17-5) TWA 1900 mg/m3 Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Components Type Ethanol (CAS 64-17-5) TWA 1000 ppm Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Components Type Ethanol (CAS 64-17-5) STEL 9500 mg/m3 5000 ppm Type Value Value	Norway. Administrative Norms for	or Contaminants in the Workpla	ace
500 ppm Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 Components Yalue Ethanol (CAS 64-17-5) TWA 1900 mg/m3 Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Components Type Value Ethanol (CAS 64-17-5) TWA 1000 ppm Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Components Type Ethanol (CAS 64-17-5) STEL 9500 mg/m3 5000 ppm Type Value Type Value	Components	Туре	Value
Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 Components Type Value Ethanol (CAS 64-17-5) TWA 1900 mg/m3 Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Value Ethanol (CAS 64-17-5) TWA 1000 ppm Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Components Type Value Value Value Ethanol (CAS 64-17-5) STEL 9500 mg/m3 Function (CAS 64-17-5) TUA 1900 mg/m3	Ethanol (CAS 64-17-5)	TLV	950 mg/m3
concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817ComponentsTypeValueEthanol (CAS 64-17-5)TWA1900 mg/m3Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) ComponentsValueEthanol (CAS 64-17-5)TWA1000 ppmRomania. OELs. Protection of workers from exposure to chemical agents at the workplace ComponentsTypeValueEthanol (CAS 64-17-5)STEL9500 mg/m3Ethanol (CAS 64-17-5)TWA1900 mg/m3			500 ppm
Ethanol (CAS 64-17-5)TWA1900 mg/m3Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) ComponentsValueEthanol (CAS 64-17-5)TWA1000 ppmRomania. OELs. Protection of workers from exposure to chemical agents at the workplace ComponentsTypeValueEthanol (CAS 64-17-5)STEL9500 mg/m3Ethanol (CAS 64-17-5)STEL9500 mg/m3TWA1900 mg/m35000 ppm	concentrations and intensities of	f harmful health factors in the	work environment, Journal of Laws 2014, item 817
Ortugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) TypeComponentsTypeValueEthanol (CAS 64-17-5)TWA1000 ppmRomania. OELs. Protection of workers from exposure to chemical agents at the workplace ComponentsValueEthanol (CAS 64-17-5)STEL9500 mg/m3 5000 ppmEthanol (CAS 64-17-5)TWA1900 mg/m3	-		1900 ma/m3
ComponentsTypeValueEthanol (CAS 64-17-5)TWA1000 ppmRomania. OELs. Protection of workers from exposure to chemical agents at the workplace ComponentsValueEthanol (CAS 64-17-5)STEL9500 mg/m3 5000 ppmTWA1900 mg/m3			-
Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Components Value Ethanol (CAS 64-17-5) STEL 9500 mg/m3 TWA 1900 mg/m3	-		
Components Type Value Ethanol (CAS 64-17-5) STEL 9500 mg/m3 5000 ppm TWA 1900 mg/m3	Ethanol (CAS 64-17-5)	TWA	1000 ppm
5000 ppm TWA 1900 mg/m3		-	
5000 ppm TWA 1900 mg/m3	Ethanol (CAS 64-17-5)	STEL	9500 mg/m3
TWA 1900 mg/m3			-
		TWA	
			-

Components	Type	of health in work with chemical agents Value	
Ethanol (CAS 64-17-5)	STEL	1920 mg/m3	
		1000 ppm	
	TWA	960 mg/m3	
		500 ppm	
Slovenia. OELs. Regulation (Official Gazette of the Regulation)		against risks due to exposure to chemicals while workin	
Components	Туре	Value	
Ethanol (CAS 64-17-5)	TWA	960 mg/m3	
		500 ppm	
Spain. Occupational Expo			
Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	1910 mg/m3	
		1000 ppm	
Sweden. OELs. Work Env Components	ironment Authority (AV), Occupationa Type	l Exposure Limit Values (AFS 2015:7) Value	
	STEL	1900 mg/m3	
(· · · · · · · · · · · · · · · · · · ·		1000 ppm	
	TWA	1000 mg/m3	
		500 ppm	
Switzerland. SUVA Grenz	worto am Arboitenlatz		
Components	Type	Value	
Ethanol (CAS 64-17-5)	STEL	1920 mg/m3	
		1000 ppm	
	TWA	960 mg/m3	
		500 ppm	
UK. EH40 Workplace Exp Components	osure Limits (WELs) Type	Value	
Ethanol (CAS 64-17-5)	TWA	1920 mg/m3	
		1000 ppm	
ogical limit values	No biological exposure limits noted f		
ommended monitoring cedures	Follow standard monitoring procedu		
ived no effect levels ELs)	Not available.		
dicted no effect centrations (PNECs)	Not available.		
osure guidelines			
Netherlands OELs (bindir	ıg): Skin designation		
Ethanol (CAS 64-17-5)		be absorbed through the skin.	
Exposure controls		-	
propriate engineering trols	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommende exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.		
vidual protection measure	es, such as personal protective equipn	nent	
General information	Use personal protective equipment a	as required. Personal protection equipment should be chose in discussion with the supplier of the personal protective	
Eye/face protection		s (or goggles). Face shield is recommended.	
Skin protection			
- Hand protection	Wear appropriate chemical resistant	gloves.	
- Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.		
	d Orshid Dasid Diffusor Dafil. 47457295	oouning. Ose of an impervious aprofilis recommended.	

Material name: Yankee Candle Wild Orchid Reed Diffuser Refill - 1745738E

Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.
Environmental exposure controls	Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties Physical state

Physical state	Liquid.
Form	Liquid.
Colour	Not available.
Odour	Not available.
Melting point/freezing point	-114 °C (-173,2 °F) estimated
Boiling point or initial boiling point and boiling range	78,4 °C (173,12 °F) estimated
Flammability	Not applicable.
Flash point	13 °C (55,4 °F) estimated
Auto-ignition temperature	365 °C (689 °F) estimated
Decomposition temperature	Not available.
рН	Not available.
Kinematic viscosity	Not available.
Solubility	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water) (log value)	Not available.
Vapour pressure	38,07839 hPa estimated
Density and/or relative density	
Density	0,831 g/cm3 estimated
Vapour density	Not available.
Particle characteristics	Not available.
9.2. Other information	
9.2.1. Information with regard to physical hazard classes	No relevant additional information available.
9.2.2. Other safety characteristic	cs
Percent volatile	89,58 % estimated
Specific gravity	0,83118 estimated
VOC	73,71 % estimated
SECTION 10: Stability and	reactivity
10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.

10.6. HazardousNo hazardous decomposition products are known.decomposition products

SECTION 11: Toxicological information

General information

Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure			
Inhalation	-	nalation may be harmful.	
Skin contact	-	allergic skin reaction.	
Eye contact	2	us eye irritation.	
Ingestion		scomfort if swallowed. However, ingestic	on is not likely to be a primary route of
Symptoms		evere eye irritation. Symptoms may inclu . Coughing. May cause an allergic skin r	ide stinging, tearing, redness, swelling, and eaction. Dermatitis. Rash.
11.1. Information on hazard cla	sses as defined	l in Regulation (EC) No 1272/2008	
Acute toxicity	No data availa	able.	
Skin corrosion/irritation	Due to partial	or complete lack of data the classification	on is not possible.
Serious eye damage/eye irritation	Causes serior	us eye irritation.	
Respiratory sensitisation	Due to partial	or complete lack of data the classification	on is not possible.
Skin sensitisation	May cause ar	n allergic skin reaction.	
Germ cell mutagenicity	Due to partial	or complete lack of data the classification	on is not possible.
Carcinogenicity	Due to partial	or complete lack of data the classification	on is not possible.
Hungary. 26/2000 EüM Ord (as amended) Not listed.	inance on prote	ection against and preventing risk rela	iting to exposure to carcinogens at work
Reproductive toxicity	Due to partial	or complete lack of data the classification	on is not possible.
Specific target organ toxicity - single exposure		or complete lack of data the classification	
Specific target organ toxicity - repeated exposure	Due to partial	or complete lack of data the classification	on is not possible.
Aspiration hazard	Due to partial	or complete lack of data the classification	on is not possible.
Mixture versus substance information	No informatio	n available.	
11.2. Information on other haza	rds		
Endocrine disrupting properties	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.		
Other information	Not available.		
SECTION 12: Ecological i	nformation		
12.1. Toxicity		uatic life with long lasting effects. Based or hazardous to the aquatic environment,	on available data, the classification criteria , acute hazard.
Components		Species	Test Results
Ethanol (CAS 64-17-5)			
Aquatic			
Acute			
Crustacea	EC50	Water flea (Daphnia magna)	7,7 - 11,2 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	42 mg/l, 4 days

12.2. Persistence and

(Oncorhynchus mykiss) No data is available on the degradability of any ingredients in the mixture.

degradability

12.3. Bioaccumulative potential

Partition coefficient

Partition coefficient	
n-octanol/water (log Kow)	
Benzoic acid, 2-hydroxy-, hexyl ester	5,5
Benzyl salicylate	4
Cyclamen aldehyde	3,4
Ethanol	-0,31
Galaxolide	5,3
Hexyl Cinnamal	4,686
Hydroxycitronellal	1,68
Linalool	2,97

Bioconcentration factor (BCF)	Not available.
12.4. Mobility in soil	No data available.
12.5. Results of PBT and vPvB assessment	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.
12.6. Endocrine disrupting properties	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.
12.7. Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.
12.8. Additional information	

Estonia Dangerous substances in soil Data

Eotorna Bangorouo cabotaneoo in con Bata	
Ethanol (CAS 64-17-5)	Chemical pesticides (As the total sum of the active substances) 0,5 mg/kg
	Chemical pesticides (As the total sum of the active substances) 20 mg/kg
	Chemical pesticides (As the total sum of the active substances) 5 mg/kg
SECTION 13: Disposal considerations	

S

13.1. Waste treatment methods	
Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

AD	ĸ	
	14.1. UN number	UN1170
	14.2. UN proper shipping name	ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) (Ethanol)
	14.3. Transport hazard class	(es)
	Class	3
	Subsidiary risk	-
	Label(s)	3
	Hazard No. (ADR)	33
	Tunnel restriction code	D/E
	14.4. Packing group	II
	14.5. Environmental hazards	No.
	14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	for user	
RID		
	14.1. UN number	UN1170
	14.2. UN proper shipping name	ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) (Ethanol)
	14.3. Transport hazard class(es)	
	Class	3
	Subsidiary risk	-
	Label(s)	3
	14.4. Packing group	II.
	14.5. Environmental hazards	No.
	14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	for user	
AD	N	
	14.1. UN number	UN1170

14.2. UN proper shipping name	ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) (Ethanol)
14.3. Transport hazard class	es)
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	II
14.5. Environmental hazards	s No.
14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
for user	
ΙΑΤΑ	
14.1. UN number	UN1170
14.2. UN proper shipping	Ethanol solution (Ethanol)
name	
14.3. Transport hazard class	
Class	3
Subsidiary risk	
14.4. Packing group	
14.5. Environmental hazards	
ERG Code	3L
14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
for user Other information	
	Allowed with restrictions
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
14.1. UN number	UN1170
14.2. UN proper shipping	ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
name	(Ethanol), MARINE POLLUTANT
14.3. Transport hazard class	(es)
Class	3
Subsidiary risk	-
14.4. Packing group	II
14.5. Environmental hazards	i
Marine pollutant	Yes
EmS	F-E, S-D
14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
for user	
14.7. Maritime transport in bulk	Not established.
according to IMO instruments	

ADN; ADR; IATA; IMDG; RID



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.
- Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended
 - Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.
- Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.
- Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

UFI:

Austria: 4CSX-WS78-9Q7H-NKVN Belgium: 4CSX-WS78-9Q7H-NKVN Bulgaria: 4CSX-WS78-9Q7H-NKVN Croatia: 4CSX-WS78-9Q7H-NKVN Cyprus: 4CSX-WS78-9Q7H-NKVN Czech Republic: 4CSX-WS78-9Q7H-NKVN Denmark: 4CSX-WS78-9Q7H-NKVN Estonia: 4CSX-WS78-9Q7H-NKVN EU: 4CSX-WS78-9Q7H-NKVN Finland: 4CSX-WS78-9Q7H-NKVN France: 4CSX-WS78-9Q7H-NKVN Germany: 4CSX-WS78-9Q7H-NKVN Great Britain: 4CSX-WS78-9Q7H-NKVN Greece: 4CSX-WS78-9Q7H-NKVN Hungary: 4CSX-WS78-9Q7H-NKVN Iceland: 4CSX-WS78-9Q7H-NKVN Ireland: 4CSX-WS78-9Q7H-NKVN Italy: 4CSX-WS78-9Q7H-NKVN Latvia: 4CSX-WS78-9Q7H-NKVN Lithuania: 4CSX-WS78-9Q7H-NKVN Luxemboura: 4CSX-WS78-9Q7H-NKVN Malta: 4CSX-WS78-9Q7H-NKVN Netherlands: 4CSX-WS78-9Q7H-NKVN Norway: 4CSX-WS78-9Q7H-NKVN Poland: 4CSX-WS78-9Q7H-NKVN Portugal: 4CSX-WS78-9Q7H-NKVN Romania: 4CSX-WS78-9Q7H-NKVN Slovakia: 4CSX-WS78-9Q7H-NKVN Slovenia: 4CSX-WS78-9Q7H-NKVN Spain: 4CSX-WS78-9Q7H-NKVN Sweden: 4CSX-WS78-9Q7H-NKVN

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Ethanol (CAS 64-17-5)

Linalool (CAS 78-70-6)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Ethanol (CAS 64-17-5) Galaxolide (CAS 1222-05-5)

Other regulations	The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.
National regulations	Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.
15.2. Chemical safety assessment	No Chemical Safety Assessment has been carried out.
SECTION 16: Other inform	nation
List of abbreviations	
	 ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways. ADR: Agreement concerning the International Carriage of Dangerous Goods by Road. AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany). CAS: Chemical Abstract Service. CEN: European Committee for Standardization. IATA: International Air Transport Association. IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk. IMDG: International Maritime Dangerous Goods. MAC: Maximum Allowed Concentration. MARPOL: International Convention for the Prevention of Pollution from Ships. PBT: Persistent, bioaccumulative and toxic. RID: Regulations concerning the International Carriage of Dangerous Goods by Rail. STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average.
	VLE: Exposure Limit Value.
	VME: Exposure Average Value. vPvB: Very persistent and very bioaccumulative.
References	Not available.
Information on evaluation method leading to the classification of mixture	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
Full text of any statements, which are not written out in full under sections 2 to 15	 H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.
Revision information	Product and Company Identification: Product and Company Identification SECTION 2: Hazards identification: Prevention SECTION 2: Hazards identification: Response SECTION 2: Hazards identification: Storage SECTION 2: Hazards identification: 2,3. Other hazards SECTION 6: Accidental release measures: 6,3. Methods and material for containment and cleaning up SECTION 6: Accidental release measures: For non-emergency personnel SECTION 7: Handling and storage: 7,2. Conditions for safe storage, including any incompatibilities SECTION 7: Handling and storage: 7,3. Specific end use(s) SECTION 11: Toxicological information: Endocrine disrupting properties SECTION 12: Ecological information: 12,6. Endocrine disrupting properties SECTION 12: Ecological information: 12,7. Other adverse effects SECTION 16: Other information: References SECTION 16: Other information: List of abbreviations
Training information	Follow training instructions when handling this material.
Disclaimer	Yankee Candle s.r.o. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.