

# slow close toilet seat

White

Complete With Fittings

Quick & Easy To Install

High Quality, Shock-proof Duroplast Material

Fits Standard UK Toilets

445 x 372 x 53mm (approx)

## Cleaning:

Wipe clean with a damp cloth.

Do not use abrasive cleaners or cleaners containing bleach.

If bleach contacts the toilet seat, rinse well and dry immediately.

## This packaging contains:

- 1 x toilet seat (1)
- 1 x right hinge (2)
- 1 x left hinge (3)
- 2 x bolts (4)
- 2 x rectangular plastic plates (5)
- 2 x plastic washers (6)
- 2 x stainless steel nuts (7)
- 2 x stainless steel brackets (8)
- 2 x stainless steel washers (9)
- 2 x plastic nut/washer combo (10)
- 1 x tightening tool (11)

Components List: Please check to ensure all the parts are included in the box. If not kindly contact your retailer

Step 1: Guide the bolt (4) through the stainless steel bracket (8).

Step 2: Once assembled, slide the bolt (4) and the stainless steel bracket (8), through the slot in hinges (2 or 3).

Step 3: To secure the bolt (4) and the stainless steel bracket (8) in place, fix the clear plastic piece (5) onto the bottom of the hinge as shown in the image.

Step 4: Insert the hinge into the toilet seat as shown and repeat step's 1 to 3 for the other side.

Step 5: Once the two hinges have been attached to the toilet seat, guide the screws carefully through the slots on your toilet bowl.

Step 6: To secure your new toilet seat, slide the clear plastic washer (6), the white plastic nut/washer combo (10), the Stainless Steel washer (9) and the Stainless Steel nut (7) up along the protruding bolt (4) from the underside of your toilet bowl. To fix in place, tighten the Stainless Steel nut with the tightening tool (11)

