



Version: 2 (04/09/2019)

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: Assam & White Cedar large wax fill ceramic FE2005

Version: 2

Section 1. Identification of the substance or the mixture and of the supplier

1.1 Product Identifier

Product identifier: Assam & White Cedar large wax fill ceramic FE2005

Other identifiers: None

Unique Formula 1391-800P-900J-A7CD

Identifier (UFI):

1.2 Relevant identified uses of the substance of mixture and uses advised against

Product uses: Home fragrance

1.3 Details of the supplier of the safety data sheet

Company name: Wax Lyrical Ltd Company address: Lindal in Furness

> Ulverston Cumbria **LA12 0LD**

Regulatory Affairs Contact:

E-Mail address: sds@wax-lyrical.co.uk

01229 461100 Company phone: 1.4 Emergency telephone number

Emergency phone: NHS 111

Section 2. Hazards identification

2.1 Classification of the substance or mixture

Classification under Regulation (EC) No 1272/2008

danger:

Class and category of Hazardous to the Aquatic Environment - Long-term Hazard Category 3

H412, Harmful to aquatic life with long lasting effects.

2.2 Label elements

Signal word: None

Hazard statements: H412, Harmful to aquatic life with long lasting effects.

Supplemental EUH208, Contains Benzyl salicylate, Linalool, alpha-Hexylcinnamaldehyde, p-t-Butyl-alpha-

Information: methylhydrocinnamic aldehyde. May produce an allergic reaction.

Precautionary P273, Avoid release to the environment.

statements: P501, Dispose of contents/container to approved disposal site, in accordance with local

regulations.

Pictograms: None



WAX LYRICAL ENGLAND

Issue date: 23/01/2020

Version: 2 (04/09/2019)

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: Assam & White Cedar large wax fill ceramic FE2005

Version: 2

Other hazards: Unique Formula Identifier: 1391-800P-900J-A7CD

Section 3. Composition / information on ingredients

3.2 Mixtures

Contains:

Name	CAS	EC	REACH Registration No.	%	Classification for (CLP) 1272/2008
p-t-Butyl-alpha- methylhydrocinnamic aldehyde	80-54-6	201-289-8		0.1-<1%	Acute Tox. 4-Skin Irrit. 2-Skin Sens. 1B-Repr. 2-Aquatic Chronic 2; H302-H315-H317- H361-H411,-
Benzyl salicylate	118-58-1	204-262-9		0.1-<1%	Skin Sens. 1B-Aquatic Chronic 3;H317-H412,-
Linalool	78-70-6	201-134-4		0.1-<1%	Skin Irrit. 2-Eye Dam. 2-Skin Sens. 1B;H315- H317-H319,-
alpha- Hexylcinnamaldehyde	101-86-0	202-983-3		0.1-<1%	Skin Sens. 1B-Aquatic Acute 1-Aquatic Chronic 2;H317-H400- H411,-
Oxacyclohexadecen-2- one	34902-57-3	422-320-3		0.1-<1%	Aquatic Acute 1- Aquatic Chronic 2; H400-H411,-
alpha-Cedrene	469-61-4	207-418-4		<0.1%	Asp. Tox 1-Aquatic Acute 1-Aquatic Chronic 1;H304-H410,-

Substances with Community workplace exposure limits:

Not Applicable

Substances that are persistent, bioaccumulative and toxic or very persistent and very bioaccumulative, greater than 0.1%:

Not Applicable

Section 4. First-aid measures

4.1 Description of first aid measures

Inhalation: Remove from exposure site to fresh air, keep at rest, and obtain medical attention.

Eye exposure: Flush immediately with water for at least 15 minutes. Contact physician if symptoms persist. **Skin exposure:** Remove contaminated clothes. Wash thoroughly with soap and water. Contact physician if

irritation persists.

Ingestion: Rinse mouth with water and obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

None expected, see Section 4.1 for further information.





Version: 2 (04/09/2019)

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: Assam & White Cedar large wax fill ceramic FE2005

Version: 2

4.3 Indication of any immediate medical attention and special treatment needed

None expected, see Section 4.1 for further information.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable media: Alcohol resistant foam, carbon dioxide, dry powder or water fog

5.2 Special hazards arising from the substance or mixture

In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

5.3 Advice for fire fighters:

In case of insufficient ventilation, wear suitable respiratory equipment.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation. Avoid contact with skin and eyes. See protective measures under Section 7 and 8.

6.2 Environmental precautions:

Keep away from drains, surface and ground water, and soil.

6.3 Methods and material for containment and cleaning up:

Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

6.4 Reference to other sections:

Also refer to sections 8 and 13.

Section 7. Handling and storage

7.1 Precautions for safe handling:

Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use personal protective equipment as required. Use in accordance with good manufacturing and industrial hygiene practices. Use in areas with adequate ventilation Do not eat, drink or smoke when using this product.

7.2 Conditions for safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.





Version: 2 (04/09/2019)

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: Assam & White Cedar large wax fill ceramic FE2005

Version: 2

7.3 Specific end use(s):

Home fragrance: Use in accordance with good manufacturing and industrial hygiene practices.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limits: Not Applicable

8.2 Exposure Controls

Eye / Skin Protection

Wear protective gloves/eye protection/face protection

Respiratory Protection

Under normal conditions of use and where adequate ventilation is available to prevent build up of excessive vapour, this material should not require special engineering controls. However, in conditions of high or prolonged use, or high temperature or other conditions which increase exposure, the following engineering controls can be used to minimise exposure to personnel: a) Increase ventilation of the area with local exhaust ventilation. b) Personnel can use an approved, appropriately fitted respirator with organic vapour cartridge or canisters and particulate filters. c) Use closed systems for transferring and processing this material.

Also refer to Sections 2 and 7.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:

Odour:

Not determined

Odour threshold:

Not determined

Evaporation rate:Not determined
Flammability (solid, gas):
Not determined

Upper/lower flammability or explosive limits: Product does not present an explosion hazard

Vapour pressure: Not determined Vapour density: Not determined Not determined Relative density: Solubility(ies): Not determined Partition coefficient: n-octanol/water: Not determined **Auto-ignition temperature:** Not determined **Decomposition temperature:** Not determined Viscosity: Not determined





Version: 2 (04/09/2019)

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: Assam & White Cedar large wax fill ceramic FE2005

Version: 2

Explosive properties: Not expected Oxidising properties: Not expected

9.2 Other information: None available

Section 10. Stability and reactivity

10.1 Reactivity:

Presents no significant reactivity hazard, by itself or in contact with water.

10.2 Chemical stability:

Good stability under normal storage conditions.

10.3 Possibility of hazardous reactions:

Not expected under normal conditions of use.

10.4 Conditions to avoid:

Avoid extreme heat.

10.5 Incompatible materials:

Avoid contact with strong acids, alkalis or oxidising agents.

10.6 Hazardous decomposition products:

Not expected.

Section 11. Toxicological information

11.1 Information on toxicological effects

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in Regulation (EC) No 1272/2008 (CLP).

This material does not meet the criteria for classification for health hazards under Regulation (EC) No 1272/2008.

Acute Toxicity: Based on available data the classification criteria are not met.

Acute Toxicity Oral Not Applicable
Acute Toxicity Dermal Not Applicable
Acute Toxicity Inhalation Not Available

Skin corrosion/irritation: Based on available data the classification criteria are not met. Based on available data the classification criteria are not met. Serious eye damage/irritation: Based on available data the classification criteria are not met. Respiratory or skin sensitisation: Germ cell mutagenicity: Based on available data the classification criteria are not met. Carcinogenicity: Based on available data the classification criteria are not met. Based on available data the classification criteria are not met. Reproductive toxicity: STOT-single exposure: Based on available data the classification criteria are not met. STOT-repeated exposure: Based on available data the classification criteria are not met. Based on available data the classification criteria are not met. **Aspiration hazard:**





Version: 2 (04/09/2019)

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: Assam & White Cedar large wax fill ceramic FE2005

Version: 2

Information about hazardous ingredients in the mixture

Not Applicable

Refer to Sections 2 and 3 for additional information.

Section 12. Ecological information

12.1 Toxicity:

Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability:Not available12.3 Bioaccumulative potential:Not available12.4 Mobility in soil:Not available

12.5 Results of PBT and vPvB assessment:

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6 Other adverse effects: Not available

Section 13. Disposal considerations

13.1 Waste treatment methods:

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Section 14. Transport information

14.1 UN number: Not classified

14.2 UN Proper Shipping Name: -

14.3 Transport hazard class(es): Not classified

Sub Risk: Not classified roup: Not classified

14.4. Packing Group: Not classified

14.5 Environmental hazards: Not environmentally hazardous for transport

14.6 Special precautions for user: None additional

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not classified

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Water Hazard Class (WGK): 2

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out for this product.

Section 16. Other information

Page 7 (8)



Issue date: 23/01/2020

Version: 2 (04/09/2019)

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: Assam & White Cedar large wax fill ceramic FE2005

Version: 2

Concentration % Limits: EH C3=69.44%

Total Fractional Values: EH C3=1.44

Key to revisions:

Classification under Regulation (EC) No 1272/2008 SECTION 3: Composition/information on ingredients

Key to abbreviations:

Abbreviation	Meaning		
Acute Tox. 4	Acute Toxicity - Oral Category 4		
Aquatic Acute 1	Hazardous to the Aquatic Environment - Acute Hazard Category 1		
Aquatic Chronic 1	Hazardous to the Aquatic Environment - Long-term Hazard Category 1		
Aquatic Chronic 2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2		
Aquatic Chronic 3	Hazardous to the Aquatic Environment - Long-term Hazard Category 3		
Asp. Tox 1	Aspiration Hazard Category 1		
Eye Dam. 2	Eye Damage / Irritation Category 2		
H302	Harmful if swallowed.		
H304	May be fatal if swallowed and enters airways.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H319	Causes serious eye irritation.		
H361	Suspected of damaging fertility or the unborn child (exposure route).		
H400	Very toxic to aquatic life.		
H410	Very toxic to aquatic life with long lasting effects.		
H411	Toxic to aquatic life with long lasting effects.		
H412	Harmful to aquatic life with long lasting effects.		
P202	Do not handle until all safety precautions have been read and understood.		
P261	Avoid breathing vapour or dust.		
P264	Wash hands and other contacted skin thoroughly after handling.		
P270	Do not eat, drink or smoke when using this product.		
P272	Contaminated work clothing should not be allowed out of the workplace.		
P273	Avoid release to the environment.		
P280	Wear protective gloves/eye protection/face protection.		
P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.		
P301/312	IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.		
P302/352	IF ON SKIN: Wash with plenty of soap and water.		
P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P308/313	IF exposed or concerned: Get medical advice/attention.		
P330	Rinse mouth.		
P331	Do not induce vomiting.		
P333/313	If skin irritation or rash occurs: Get medical advice/attention.		





Version: 2 (04/09/2019)

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: Assam & White Cedar large wax fill ceramic FE2005

Version: 2

P337/313	If eye irritation persists: Get medical advice/attention.		
P362	Take off contaminated clothing and wash before reuse.		
P363	Wash contaminated clothing before reuse.		
P391	Collect spillage.		
P405	Store locked up.		
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.		
Repr. 2	Toxic to Reproduction Category 2		
Skin Irrit. 2	Skin Corrosion / Irritation Category 2		
Skin Sens. 1B	Sensitization - Skin Category 1B		

The information in this safety data sheet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.