

SAFETY DATA SHEET

In accordance with GB REACH UK SI 2020 No. 1577

Product: R/D Refill 200ml Clarity SC1406

Version: 1

Section 1. Identification of the substance or the mixture and of the supplier

1.1 Product Identifier

Product identifier: R/D Refill 200ml Clarity SC1406

Other identifiers: None

Unique Formula Identifier (UFI): USR1-304K-0001-V5EX

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product uses: Home fragrance

1.3 Details of the supplier of the safety data sheet

Company name: Wax Lyrical Ltd

Company address: Lindal in Furness
Ulverston
Cumbria
LA12 0LD

Contact: Regulatory Affairs

E-Mail address: sds@wax-lyrical.co.uk

Company phone: 01229 461100

1.4 Emergency telephone number

Emergency phone: NHS 111 (for HCP - NPIS 0344 892 0111)

Section 2. Hazards identification

2.1 Classification of the substance or mixture

Classification under GB GHS UK SI 2020 No. 1567

Class and category of danger: Flammable Liquid, Hazard Category 2
Eye Damage / Irritation Category 2
Hazardous to the Aquatic Environment - Long-term Hazard Category 3
H225, Highly flammable liquid and vapour.
H319, Causes serious eye irritation.
H412, Harmful to aquatic life with long lasting effects.

2.2 Label elements

Classification under GB GHS UK SI 2020 No. 1567

Signal word: Danger

Hazard statements: H225, Highly flammable liquid and vapour.
H319, Causes serious eye irritation.
H412, Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

In accordance with GB REACH UK SI 2020 No. 1577

Product: R/D Refill 200ml Clarity SC1406

Version: 1

Supplemental Information: EUH208, Contains 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone, Acetyl cedrene. May produce an allergic reaction.

Precautionary statements:

P210, Keep away from heat, sparks, open flames and hot surfaces. - No smoking.
P233, Keep container tightly closed.
P240, Ground/bond container and receiving equipment.
P241, Use explosion-proof electrical, ventilating and lighting equipment.
P242, Use only non-sparking tools.
P243, Take precautionary measures against static discharge.
P264, Wash hands and other contacted skin thoroughly after handling.
P273, Avoid release to the environment.
P280, Wear protective gloves/eye protection/face protection.
P303/361/353, IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P305/351/338, IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337/313, If eye irritation persists: Get medical advice/attention.
P370/378, In case of fire: Use carbon dioxide, dry chemical, foam for extinction.
P403/235, Store in a well-ventilated place. Keep cool.
P501, Dispose of contents/container to approved disposal site, in accordance with local regulations.

Pictograms:



2.3 Other hazards

Other hazards:

Sensitisers declared on a CLP Hazard Label: 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone, Acetyl cedrene
Hydrocarbon Concentration %: 0.0000%
Unique Formula Identifier: USR1-304K-0001-V5EX

Section 3. Composition / information on ingredients

3.2 Mixtures

Contains:

Name	CAS	EC	GB REACH Registration No.	%	GB GHS UK SI 2020 No. 1567
Ethyl alcohol	64-17-5	200-578-6		50-100%	Flam. Liq. 2-Eye Irrit. 2; H225-H319,-

SAFETY DATA SHEET

In accordance with GB REACH UK SI 2020 No. 1577

Product: R/D Refill 200ml Clarity SC1406

Version: 1

Isopropyl alcohol	67-63-0	200-661-7		10-<20%	Flam. Liq. 2-Eye Irrit. 2-STOT SE 3;H225-H319-H336,-
3-(5,5,6-Trimethylbicyclo [2.2.1]hept-2-yl) cyclohexan-1-ol	3407-42-9	222-294-1		1-<5%	Aquatic Acute 1-Aquatic Chronic 2; H400-H411,-
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone	54464-57-2	915-730-3		0.1-<1%	Skin Irrit. 2-Skin Sens. 1B-Aquatic Chronic 2; H315-H317-H411,-
Acetyl cedrene	32388-55-9	251-020-3		0.1-<1%	Skin Sens. 1B-Aquatic Acute 1-Aquatic Chronic 1;H317-H410,-

GB workplace exposure limits:

Name	CAS	EC	GB REACH Registration No.	%	GB GHS UK SI 2020 No. 1567
Dipropylene glycol monomethyl ether	34590-94-8	252-104-2		10-<20%	-,-,-
Ethyl alcohol	64-17-5	200-578-6		50-100%	Flam. Liq. 2-Eye Irrit. 2; H225-H319,-
Isopropyl alcohol	67-63-0	200-661-7		10-<20%	Flam. Liq. 2-Eye Irrit. 2-STOT SE 3;H225-H319-H336,-

Substances that are persistent, bioaccumulative and toxic or very persistent and very bioaccumulative, greater than 0.1%:

Not Applicable

Section 4. First-aid measures

4.1 Description of first aid measures

Inhalation: Remove from exposure site to fresh air, keep at rest, and obtain medical attention.

Eye exposure: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Skin exposure: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

Ingestion: Rinse mouth with water and obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

None expected, see Section 4.1 for further information.

Section 5: Firefighting measures

5.1 Extinguishing media

Suitable media: Alcohol resistant foam,carbon dioxide,dry powder or water fog

SAFETY DATA SHEET

In accordance with GB REACH UK SI 2020 No. 1577

Product: R/D Refill 200ml Clarity SC1406

Version: 1

5.2 Special hazards arising from the substance or mixture

In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

5.3 Advice for fire fighters:

In case of insufficient ventilation, wear suitable respiratory equipment.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation. Avoid contact with skin and eyes. See protective measures under Section 7 and 8.

6.2 Environmental precautions:

Keep away from drains, surface and ground water, and soil.

6.3 Methods and material for containment and cleaning up:

Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

6.4 Reference to other sections:

Also refer to sections 8 and 13.

Section 7. Handling and storage

7.1 Precautions for safe handling:

Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

7.2 Conditions for safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

7.3 Specific end use(s):

Home fragrance: Use in accordance with good manufacturing and industrial hygiene practices.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limits:

SAFETY DATA SHEET

In accordance with GB REACH UK SI 2020 No. 1577

Product: R/D Refill 200ml Clarity SC1406

Version: 1

Ingredient	CAS	EC	Description	Value
Dipropylene glycol monomethyl ether	34590-94-8	252-104-2	UK WEL Long term mgm3	308
			UK WEL Long term ppm	50
Ethyl alcohol	64-17-5	200-578-6	UK WEL Long term mgm3	1920
			UK WEL Long term ppm	1000
Isopropyl alcohol	67-63-0	200-661-7	UK WEL Long term mgm3	999
			UK WEL Long term ppm	400
			UK WEL Short term mgm3	1250
			UK WEL Short term ppm	500

8.2 Exposure Controls

Eye / Skin Protection

Wear protective gloves/eye protection/face protection

Respiratory Protection

Ensure adequate and ongoing ventilation is maintained in order to prevent build up of excessive vapour and to ensure occupational exposure limits are adhered to. If appropriate, and depending on your patterns and volumes of use, the following engineering controls may be required as additional protective measures: a) Isolate mixing rooms and other areas where this material is used or openly handled. Maintain these areas under negative air pressure relative to the rest of the plant. b) Employ the use of Personal protective equipment - an approved, properly fitted respirator with organic vapour cartridges or canisters and particulate filters. c) Use local exhaust ventilation around open tanks and other open sources of potential exposures in order to avoid excessive inhalation, including places where this material is openly weighed or measured. In addition, use general dilution ventilation of the work area to eliminate or reduce possible worker exposures. d) Use closed systems for transferring and processing this material.

Also refer to Sections 2 and 7.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Not determined
Odour:	Not determined
Odour threshold:	Not determined
pH:	Not determined
Melting point / freezing point:	Not determined
Initial boiling point / range:	Not determined

SAFETY DATA SHEET

In accordance with GB REACH UK SI 2020 No. 1577

Product: R/D Refill 200ml Clarity SC1406

Version: 1

Flash point:	22 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Upper/lower flammability or explosive limits:	Product does not present an explosion hazard
Vapour pressure:	Not determined
Vapour density:	Not determined
Relative density:	Not determined
Solubility(ies):	Not determined
Partition coefficient: n-octanol/water:	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Not expected
Oxidising properties:	Not expected

9.2 Other information: None available

Section 10. Stability and reactivity

10.1 Reactivity:

Presents no significant reactivity hazard, by itself or in contact with water.

10.2 Chemical stability:

Good stability under normal storage conditions.

10.3 Possibility of hazardous reactions:

Not expected under normal conditions of use.

10.4 Conditions to avoid:

Avoid extreme heat.

10.5 Incompatible materials:

Avoid contact with strong acids, alkalis or oxidising agents.

10.6 Hazardous decomposition products:

Not expected.

Section 11. Toxicological information

11.1 Information on toxicological effects

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in GB GHS UK SI 2020 No. 1567.

Acute Toxicity:	Based on available data the classification criteria are not met.
Acute Toxicity Oral	Not Applicable
Acute Toxicity Dermal	Not Applicable

SAFETY DATA SHEET

In accordance with GB REACH UK SI 2020 No. 1577

Product: R/D Refill 200ml Clarity SC1406

Version: 1

Acute Toxicity Inhalation Not Available
Skin corrosion/irritation: Based on available data the classification criteria are not met.
Serious eye damage/irritation: Eye Damage / Irritation Category 2
Respiratory or skin sensitisation: Based on available data the classification criteria are not met.
Germ cell mutagenicity: Based on available data the classification criteria are not met.
Carcinogenicity: Based on available data the classification criteria are not met.
Reproductive toxicity: Based on available data the classification criteria are not met.
STOT-single exposure: Based on available data the classification criteria are not met.
STOT-repeated exposure: Based on available data the classification criteria are not met.
Aspiration hazard: Based on available data the classification criteria are not met.

Information about hazardous ingredients in the mixture

Not Applicable

Refer to Sections 2 and 3 for additional information.

Section 12. Ecological information

12.1 Toxicity:

Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability: Not available

12.3 Bioaccumulative potential: Not available

12.4 Mobility in soil: Not available

12.5 Results of PBT and vPvB assessment:

This substance does not meet the PBT/vPvB criteria of GB REACH UK SI 2020 No. 1577.

12.6 Other adverse effects: Not available

Section 13. Disposal considerations

13.1 Waste treatment methods:

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Section 14. Transport information

	14.1 UN number:	14.2 UN Proper Shipping Name:	14.3 Transport hazard class (es):	Sub Risk:	14.4 Packing Group:
UN Model Regulations	UN1993	FLAMMABLE LIQUID, N.O.S. (Ethyl alcohol, Isopropyl alcohol)	3	-	II
IMDG	UN1993	FLAMMABLE LIQUID, N.O.S. (Ethyl alcohol, Isopropyl alcohol)	3	-	II
ADR,RID,ADN	UN1993	FLAMMABLE LIQUID, N.O.S. (Ethyl alcohol, Isopropyl alcohol)	3	-	II

SAFETY DATA SHEET

In accordance with GB REACH UK SI 2020 No. 1577

Product: R/D Refill 200ml Clarity SC1406

Version: 1

ICAO TI	UN1993	FLAMMABLE LIQUID, N.O.S. (Ethyl alcohol, Isopropyl alcohol)	3	-	II
---------	--------	---	---	---	----

14.5 Environmental hazards: Not environmentally hazardous for transport

14.6 Special precautions for user: None additional

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not applicable

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Water Hazard Class (WGK): 2

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out for this product.

Section 16. Other information

Concentration % Limits: EDI 2=14.83% EH C3(GB)=61.46%

Total Fractional Values: EDI 2=6.75 EH C3(GB)=1.63

Key to revisions:

Not applicable

Key to abbreviations:

Abbreviation	Meaning
Aquatic Acute 1	Hazardous to the Aquatic Environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the Aquatic Environment - Long-term Hazard Category 1
Aquatic Chronic 2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2
Eye Irrit. 2	Eye Damage / Irritation Category 2
Flam. Liq. 2	Flammable Liquid, Hazard Category 2
H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
P210	Keep away from heat, sparks, open flames and hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use only non-sparking tools.

SAFETY DATA SHEET

In accordance with GB REACH UK SI 2020 No. 1577

Product: R/D Refill 200ml Clarity SC1406

Version: 1

P243	Take precautionary measures against static discharge.
P261	Avoid breathing vapour or dust.
P264	Wash hands and other contacted skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection/face protection.
P302/352	IF ON SKIN: Wash with plenty of soap and water.
P303/361/353	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304/340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P333/313	If skin irritation or rash occurs: Get medical advice/attention.
P337/313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P370/378	In case of fire: Use carbon dioxide, dry chemical, foam for extinction.
P391	Collect spillage.
P403/233/235	Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P403/235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.
STOT SE 3	Specific Target Organ Toxicity (Single Exposure) Category 3
Skin Irrit. 2	Skin Corrosion / Irritation Category 2
Skin Sens. 1B	Sensitization - Skin Category 1B

The information in this safety data sheet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.